

Safety Data Sheet**suter-kunststoffe ag**
swiss-composite.ch

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Release spray TRS

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricants, greases, release products

1.3. Details of the supplier of the safety data sheet

Company name: Suter Kunststoffe AG
 Composite Technology
 Street: Aefligenstrasse
 Place: CH 3312 Fraubrunnen ..
 Post-office box: ..
 +41 31 763 60 60

Telephone:
 e-mail: Info@swiss-composite.ch
 Internet: www.swiss-composite.ch
 Responsible Department:

1.4. Emergency telephone number:

Management
 poison information centre Tel 145

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:
 Aerosol: Aerosol 1
 Skin corrosion/irritation: Skin Irrit. 2
 Serious eye damage/eye irritation: Eye Irrit. 2
 Specific target organ toxicity - single exposure: STOT SE 3
 Hazardous to the aquatic environment: Aquatic Chronic 2
 Hazard Statements:
 Extremely flammable aerosol.
 Pressurised container: May burst if heated.
 Causes skin irritation.
 May cause drowsiness or dizziness.
 Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Kohlenwasserstoffe, C7, n-Alkane, Isoalkane, Cycloalkane
 Kohlenwasserstoffe, C7-C9, n-Alkane, Isoalkane, Cycloalkane
 Kohlenwasserstoffe, C6-C7, n-Alkane, Isoalkane, Cycloalkane, <5% n-Hexan
 Kohlenwasserstoffe, C9-C10, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten

Signal word: Danger**Pictograms:**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 2 of 13

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P312	Call a POISON CENTER/doctor if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			30 - < 35 %
	265-151-9	649-328-00-1	01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			5 - < 10 %
	265-151-9	649-328-00-1	01-2119473851-33	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411			
78-92-2	butan-2-ol			1 - < 5 %
	201-158-5	603-127-00-5		
	Flam. Liq. 3, Eye Irrit. 2, STOT SE 3, STOT SE 3; H226 H319 H335 H336			
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha			1 - < 5 %
	265-150-3	649-327-00-6	01-2119471843-32	
	Flam. Liq. 3, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H315 H336 H304 H411 EUH066			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 3 of 13

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing and wash it before reuse. Put victim at rest, cover with a blanket and keep warm. Do not leave affected person unattended. Move a vomiting patient lying on his back into a stable position on his side. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. Never give anything by mouth to an unconscious person or a person with cramps. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Self-protection of the first aider : Personal protection equipment: see section 8 First Aid.

Notes to physician: No special measures are necessary.

After inhalation

Remove victim out of the danger area. Provide fresh air. In the case of lung irritation: Primary treatment using corticoide spray, eg. Auxilolon spray, Pulmicort-dosage-spray. (Auxilolon and Pulmicort are registered trademarks). Call a physician immediately. Consult a doctor immediately in the case of inhaling spray mist and show him packing or label. Consult a doctor immediately in the case of inhaling spray mist and show him packing or label.

After contact with skin

Wash immediately with: water and soap. Rub greasy ointment into the skin.
Do not wash with: Solvents/Thinner
In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Do NOT induce vomiting. Give nothing to eat or drink. Never give anything by mouth to an unconscious person or a person with cramps. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Cough, Dyspnoea , Cyanosis (blue coloured blood), Acidosis, Central nervous system depression, Headache, Nausea, Drowsiness, Dizziness, Inebriation, Unconsciousness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water mist, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Fire rating: B (Fires of liquids or liquid turning substances).

Unsuitable extinguishing media

High power water jet, Water spray jet

5.2. Special hazards arising from the substance or mixture

Gases emitted by burning organic materials must always be classified as respiratory poisons. Burning produces heavy smoke.

Hazardous combustion products:

Carbon monoxide Carbon dioxide (CO₂), Hydrocarbons, Pyrolysis products, toxic.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 4 of 13

5.3. Advice for firefighters

Usual measures for fire prevention. Co-ordinate fire-fighting measures to the fire surroundings. In case of fire and/or explosion do not breathe fumes. In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still. Beware of reignition. Use caution when applying carbon dioxide in confined spaces. Carbon dioxide can displace oxygen. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Fire residue and contaminated firefighting water must be disposed of in accordance with government regulations.

Additional information

Special protective equipment for firefighters: Wear a self-contained breathing apparatus and chemical protective clothing. DIN-/EN-Norms: 469

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes, and clothing. Do not breathe vapour/aerosol. Remove all sources of ignition. Move persons to safety. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction. Provide adequate ventilation.

For non-emergency personnel Use personal protection equipment.

For emergency responders: Use personal protection equipment. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Ensure waste is collected and contained. Suppress gases/vapours/mists with water spray jet. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Prevent spread over a wide area (e.g. by containment or oil barriers). Remove from the water surface (e.g. skimming, sucking). Cover drains.

For cleaning up: Methods of cleaning - large amounts of spilled material Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

Methods of cleaning - small amounts of spilled material Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Collect in closed and suitable containers for disposal. Clear contaminated areas thoroughly.

Clean with detergents. Solvent use Retain contaminated washing water and dispose it. Ensure all waste water is collected and treated via a waste water treatment plant. Ventilate affected area.

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Measures to prevent aerosol and dust generation

It is recommended to design all work processes always so that the following is excluded: Inhalation of vapours or spray/mists, Eye contact, skin contact.

Technical ventilation of workplace. Vapours are heavier than air. Provide room air exhaust at ground level.

During filling, metering and sampling should be used if possible: Splashproof grounded devices. Devices with

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 5 of 13

local exhaust Use only in a exhaust booth with integrated air filter. Use in ventilated spray booths only. Ensure that fresh air is supplied to the breathing zone of the operator and exhaust air is removed in his back!
Re-circulation of exhaust air is not recommended.

Advice on protection against fire and explosion

Measures to prevent fire :

Extremely flammable. Vapours can form potentially explosive mixtures with air. Reignition possible over considerable distance. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Use only non-sparking tools. Flammable vapours can accumulate in head space of closed systems. Only use the material in places where open light, fire and other flammable sources can be kept away. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Usual measures for fire prevention. Wear anti-static footwear and clothing

Further information on handling

Environmental precautions:

Shafts and sewers must be protected from entry of the product. Transfer wash-downs in sealed containers. For restriction of emission on volatile organic compounds (VOC) the solvent vapours should be supplied to an exhaust air purification facility (filter, gas washer, incineration).

Advices on general occupational hygiene :

Use personal protection equipment. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. General health and safety measures The usual precautions when handling chemicals must be observed. Working places should be designed to allow cleaning at any time . Floors, walls and other surfaces in the hazard area must be cleaned regularly. Clean spray booth and exhaust hood completely with every product change. When using do not eat, drink, smoke, sniff. Thorough skin-cleansing after handling the product. Used working clothes should not be worn outside the work area.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Suitable floor material: Floors should be impervious, resistant to liquids and easy to clean.

Protect against: heat, Cold.

Recommended temperature for storage: +10 - +30°C

Keep away from: Food and feedingstuffs

Keep/Store only in original container.

Advice on storage compatibility

Do not store together with:

Explosive hazardous substances, Other potentially explosive hazardous substances, flammable solids, Pyrophoric or self-heating substances, Hazardous substances that release flammable gases when in contact with water, Highly oxidising substances, Oxidising substances, Ammonium nitrate and preparations containing ammonium nitrate, Organic peroxides and self-reactive substances, Infectious substances, Radioactive substances

Further information on storage conditions

Technical measures and storage conditions

The applicable provisions of the water and building legislation must be observed. Heating causes rise in pressure with risk of bursting. Keep away from sources of ignition. - No smoking. Keep in a cool, well-ventilated place. Keep receptacles tightly sealed. Protect containers against damage. Ensure adequate ventilation of the storage area. Store small packages in a suitable, robust cabinet. Do not store out of doors.

7.3. Specific end use(s)

Lubricants, greases, release products

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 6 of 13

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-92-2	Butan-2-ol	100	308		TWA (8 h)	WEL
		150	462		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Combination filtering device (EN 14387) A1P1/A2P2

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: Aerosol
 Colour: white
 Odour: characteristic

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: >- 42 °C

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 7 of 13

Flash point: > - 97 °C

Flammability

Solid: not applicable

Gas: not applicable

Lower explosion limits: 0,6 vol. %

Upper explosion limits: 9,8 vol. %

Ignition temperature: > 200 °C

Auto-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidizing.

Vapour pressure:
(at 20 °C) < 3000 hPaVapour pressure:
(at 50 °C) < 7000 hPaDensity (at 20 °C): 0,645 g/cm³Water solubility:
(at 20 °C) < 50 g/L**Solubility in other solvents**

miscible with most organic solvents

Partition coefficient: not determined

Vapour density: > 2,0

Evaporation rate: not determined

Solvent content: 56 %

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Keep away from sources of heat and ignition.

10.5. Incompatible materials

Oxidising agent

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 8 of 13

11.1. Information on toxicological effects**Acute toxicity**

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			
	oral	LD50 > 5840 mg/kg	Rat	
	dermal	LD50 > 2800 mg/kg	Rat	
	inhalative (4 h) vapour	LC50 > 23,3 mg/l	Rat	
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			
	oral	LD50 > 5840 mg/kg	Rat	
	dermal	LD50 > 2800 mg/kg	Rat	
	inhalative (4 h) vapour	LC50 > 23,3 mg/l	Rat	
78-92-2	butan-2-ol			
	oral	LD50 2190 mg/kg	Rat	GESTIS
	inhalative (4 h) vapour	LC50 48,5 mg/l	Rat	
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha			
	oral	LD50 > 5000 mg/kg	Rat	
	dermal	LD50 > 2000 mg/kg	Rat	
	inhalative (4 h) vapour	LC50 > 5,6 mg/l	Rat	

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 9 of 13

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha				
	Acute fish toxicity	LC50 > 13,4 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 10-30 mg/l	72 h	Pseudokirchnerella subcapitata	
	Acute crustacea toxicity	EC50 3 mg/l	48 h	Daphnia magna (Big water flea)	
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha				
	Acute fish toxicity	LC50 3-10 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 10-30 mg/l	72 h	Pseudokirchnerella subcapitata	
	Acute crustacea toxicity	EC50 4,6-10 mg/l	48 h	Daphnia magna (Big water flea)	
78-92-2	butan-2-ol				
	Acute fish toxicity	LC50 3670 mg/l	96 h	Pimephales promelas	GESTIS
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha				
	Acute fish toxicity	LC50 10-30 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchnerella subcapitata	
	Acute crustacea toxicity	EC50 22-46 mg/l	48 h	Daphnia magna (Big water flea)	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			
	OECD 301F, C.4-D	98%	28	
	Readily biodegradable (according to OECD criteria).			
78-92-2	butan-2-ol			
	OECD 301E, C.4-B	> 98%	19	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-92-2	butan-2-ol	0,65

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

Keine Daten verfügbar.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 10 of 13

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150111 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers
Classified as hazardous waste.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Transport category: 2
 Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 11 of 13

14.3. Transport hazard class(es): 2

14.4. Packing group: -

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Other applicable information (inland waterways transport)

E0

Marine transport (IMDG)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS (Naphtha (Petroleum), hydrotreated, light)

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL

Excepted quantity: E0

EmS: F-D, S-U

Air transport (ICAO)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

E0

Passenger-LQ: Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 12 of 13

Danger releasing substance: Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 97 %

Additional information

Aerosol directive (75/324/EEC)

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has been carried out.

SECTION 16: Other information**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Release spray TRS

Print date: 02.12.2016

Product code: 165105

Page 13 of 13

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)