

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.07.2021

Version number 1

Revision: 26.07.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Silikon-EX 2609
- **Article number:** 1383
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Product category** PC35 Washing and cleaning products (including solvent based products)
- **Application of the substance / the mixture** Cleaning agent/ Cleaner
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
WINOIL AG  
Unterdorfstrasse 37  
CH-4658 Däniken SO  
Tel. +41 62 288 11 11
- **Further information obtainable from:**  
Abteilung Labor  
info@winoil.ch
- **1.4 Emergency telephone number:**  
Tox Info Suisse  
24-h-Emergency number: 145 (from abroad: +41 44 251 51 51)  
Information: +41 44 251 66 66

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2      H225      Highly flammable liquid and vapour.



GHS08 health hazard

STOT RE 1      H372      Causes damage to organs through prolonged or repeated exposure.  
Asp. Tox. 1      H304      May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2 H411      Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2      H315      Causes skin irritation.  
Eye Irrit. 2      H319      Causes serious eye irritation.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 26.07.2021

Version number 1

Revision: 26.07.2021

Trade name: **Silikon-EX 2609**

(Contd. of page 1)

STOT SE 3      H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms



GHS02   GHS07   GHS08   GHS09

#### Signal word Danger

#### Hazard-determining components of labelling:

xylene

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane

#### Hazard statements

H225      Highly flammable liquid and vapour.

H315      Causes skin irritation.

H319      Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H372      Causes damage to organs through prolonged or repeated exposure.

H304      May be fatal if swallowed and enters airways.

H411      Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.

P273      Avoid release to the environment.

P280      Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P501      Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

- PBT: Not applicable.

- vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Chemical characterisation: Mixtures

- Description: Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7	xylene <ul style="list-style-type: none"> <li> Flam. Liq. 3, H226;  STOT RE 2, H373;  Asp. Tox. 1, H304;</li> <li> Acute Tox. 4, H312;  Acute Tox. 4, H332;  Skin Irrit. 2, H315;  Eye Irrit. 2, H319;  STOT SE 3, H335</li> </ul>	25-50%
EC number: 920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics <ul style="list-style-type: none"> <li> Flam. Liq. 2, H225;  Asp. Tox. 1, H304;  Aquatic Chronic 2, H411;  STOT SE 3, H336</li> </ul>	25-50%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 26.07.2021

Version number 1

Revision: 26.07.2021

Trade name: **Silikon-EX 2609**

(Contd. of page 2)

EC number: 921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
EC number: 919-446-0	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	10-25%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

##### · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

##### · After skin contact: Immediately wash with water and soap and rinse thoroughly.

##### · After eye contact: Rinse opened eye for several minutes under running water.

##### · After swallowing: Do not induce vomiting; call for medical help immediately.

#### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

##### · Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

##### · For safety reasons unsuitable extinguishing agents: Water with full jet

#### · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

#### · 5.3 Advice for firefighters

##### · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

#### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

CH/

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 26.07.2021

Version number 1

Revision: 26.07.2021

Trade name: **Silikon-EX 2609**

(Contd. of page 3)

### 6.4 Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

## SECTION 7: Handling and storage

- 7.1 **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- 7.1 **Information about fire - and explosion protection:**
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.
- 7.2 **Conditions for safe storage, including any incompatibilities**
- 7.2 **Storage:**
  - Requirements to be met by storerooms and receptacles: Store in a cool location.
  - Information about storage in one common storage facility: Store away from oxidising agents.
  - Further information about storage conditions:
    - Keep container tightly sealed.
    - Store in cool, dry conditions in well sealed receptacles.
- 7.3 **Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- 8.1 **Control parameters**
- Additional information about design of technical facilities: No further data; see item 7.

### Ingredients with limit values that require monitoring at the workplace:

#### 1330-20-7 xylene

MAK (Switzerland)	Short-term value: 870 mg/m <sup>3</sup> , 200 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm H B;
-------------------	---

### Ingredients with biological limit values:

#### 1330-20-7 xylene

BAT (Switzerland)	1,5 g/g Kreatinin Untersuchungsmaterial: Urin Probennahmezeitpunkt: bei Langzeitexposition: Nach mehreren vorangegangenen Schichten, Expositionsende bzw. Schichtende Biol. Parameter: Methyl-Hippursäure  1,5 mg/l Untersuchungsmaterial: Vollblut Probennahmezeitpunkt: Expositionsende bzw. Schichtende Biol. Parameter: Xylol
-------------------	---

- Additional information: The lists valid during the making were used as basis.

### 8.2 Exposure controls

- Personal protective equipment:
- General protective and hygienic measures:
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.
  - Store protective clothing separately.
  - Avoid contact with the skin.

(Contd. on page 5)

CH/

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 26.07.2021

Version number 1

Revision: 26.07.2021

Trade name: **Silikon-EX 2609**

(Contd. of page 4)

Avoid contact with the eyes and skin.

· **Respiratory protection:**

If engineering measures cannot maintain the concentration of pollutants in the air at a level sufficient for worker health, approved respiratory protection may be appropriate.

Filter AX

· **Protection of hands:**



Protective gloves

Wear suitable gloves.

Chemical protection gloves are suitable, which are tested according to EN 374.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned below together with the supplier of these gloves.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	Colourless
<b>Odour:</b>	Petrol-like
<b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	60 °C

· **Flash point:** -25 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 250 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

(Contd. on page 6)

CH/

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.07.2021

Version number 1

Revision: 26.07.2021

Trade name: **Silikon-EX 2609**

(Contd. of page 5)

· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
Lower:	0,6 Vol %
Upper:	7,3 Vol %
· <b>Vapour pressure at 20 °C:</b>	190 hPa
· <b>Density at 20 °C:</b>	0,788 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
· <b>Solvent content:</b>	
Organic solvents:	100,0 %
Solids content:	0,0 %
· <b>9.2 Other information</b>	No further relevant information available.

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**1330-20-7 xylene**

Oral	LD50	4.300 mg/kg (rat)
Dermal	LD50	2.000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 7)

CH/

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 26.07.2021

Version number 1

Revision: 26.07.2021

Trade name: **Silikon-EX 2609**

(Contd. of page 6)

- **Additional toxicological information:**
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure**  
Causes damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

14 00 00	WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08)
14 06 00	waste organic solvents, refrigerants and foam/aerosol propellants
14 06 03*	other solvents and solvent mixtures

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

CH/

(Contd. on page 8)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.07.2021




Version number 1

Revision: 26.07.2021

Trade name: **Silikon-EX 2609**

(Contd. of page 7)

## SECTION 14: Transport information

<ul style="list-style-type: none"> <li>· <b>14.1 UN-Number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	UN1268
<ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul>	UN1268 PETROLEUM DISTILLATES, N.O.S., ENVIRONMENTALLY HAZARDOUS PETROLEUM DISTILLATES, N.O.S. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane), MARINE POLLUTANT PETROLEUM DISTILLATES, N.O.S.
<ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR, IMDG</b></li> </ul>	<div style="display: flex; align-items: center; gap: 10px;">   </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>
<ul style="list-style-type: none"> <li>· <b>IATA</b></li> </ul>	<div style="display: flex; align-items: center; gap: 10px;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>
<ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	II
<ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> <li>· <b>Special marking (ADR):</b></li> </ul>	Product contains environmentally hazardous substances: Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Yes Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul>	Warning: Flammable liquids. 33 F-E, S-E B
<ul style="list-style-type: none"> <li>· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b></li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>ADR</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 9)

CH/



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 26.07.2021

Version number 1

Revision: 26.07.2021

Trade name: **Silikon-EX 2609**

(Contd. of page 8)

· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D/E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Abteilung Labor
- **Contact:** Laborleiter Winoil AG
- **Abbreviations and acronyms:**  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 2: Flammable liquids – Category 2  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1

(Contd. on page 10)

CH/

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 26.07.2021

Version number 1

Revision: 26.07.2021

**Trade name: Silikon-EX 2609***Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

(Contd. of page 9)

**\* Data compared to the previous version altered.**

GH/