

Safety Data Sheet

according to UK REACH Regulation

Hardener S

Revision date: 04.05.2022

Product code: 100140

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Hardener S

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

epoxy resin hardener

1.3. Details of the supplier of the safety data sheet

Company name:	Suter Kunststoffe AG	Telephone:	+41 (0)31 763 60 60	Telefax:	+41 (0)31 763 60 61
Street:	Aefligenstrasse 3	e-mail:	info@swiss-composite.ch		
Place:	CH-3312 Fraubrunnen	Internet:	www.swiss-composite.ch		
		Responsible Department:	Sales Team		

1.4. Emergency telephone**number:**

Tox Info Suisse 145

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1A

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1

Reproductive toxicity: Repr. 2

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Harmful if swallowed.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

Suspected of damaging the unborn child.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

Phenol, styrenated

2,2,4-trimethylhexane-1,6-diamine

m-phenylenebis(methylamine)

Phenol, methylstyrenated

salicylic acid

Polyoxypropylenediamine

Signal word: Danger**Pictograms:****Hazard statements**

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H361d	Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P310	Immediately call a POISON CENTER/doctor.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.

Safety Data Sheet

according to UK REACH Regulation

Hardener S

Revision date: 04.05.2022

Product code: 100140

Page 2 of 10

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	GHS Classification	
61788-44-1	Phenol, styrenated	25 - 50 %
	262-975-0	01-2119979575-18
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411	
25513-64-8	2,2,4-trimethylhexane-1,6-diamine	10 - 25 %
	247-063-2	01-2119560598-25
	Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H302 H314 H317 H412	
1477-55-0	1,3-Benzoldimethanamine	10 - 25 %
	216-032-5	01-2119480150-50
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H332 H302 H314 H317 H412 EUH071	
68512-30-1	Phenol, methylstyrenated	10 - 25 %
	270-966-8	01-2119555274-38
	Acute Tox. 4, Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H312 H315 H317 H412	
69-72-7	salicylic acid	2,5 - 10 %
	200-712-3	607-732-00-5
	01-2119486984-17	
	Repr. 2, Acute Tox. 4, Eye Dam. 1; H361d H302 H318	
9046-10-0	Polyoxypropylenediamine	2,5 - 10 %
	618-561-0	01-2119557899-12
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Chronic 3; H302 H314 H318 H412	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
61788-44-1	262-975-0	Phenol, styrenated	25 - 50 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	
25513-64-8	247-063-2	2,2,4-trimethylhexane-1,6-diamine	10 - 25 %
		oral: LD50 = 910 mg/kg	
1477-55-0	216-032-5	1,3-Benzoldimethanamine	10 - 25 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 3100 mg/kg; oral: LD50 = 980 mg/kg	
68512-30-1	270-966-8	Phenol, methylstyrenated	10 - 25 %
		dermal: LD50 = 2000 mg/kg; oral: LD50 = 3600 mg/kg	
69-72-7	200-712-3	salicylic acid	2,5 - 10 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 891 mg/kg	
9046-10-0	618-561-0	Polyoxypropylenediamine	2,5 - 10 %
		dermal: LD50 = 2090 mg/kg; oral: LD50 = 475 mg/kg	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated clothing immediately. Pay attention to self-protection.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

Safety Data Sheet

according to UK REACH Regulation

Hardener S

Revision date: 04.05.2022

Product code: 100140

Page 3 of 10

After contact with skin

Immediately with water and soap and rinse thoroughly. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Drink plenty of water and fresh air. Call a doctor immediately

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Extinguishing powder, Water spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire: Formation of: Gases/vapours, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin, eyes and clothes. Wearing a personal protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter the soil or subsoil.

6.3. Methods and material for containment and cleaning up

Provide adequate ventilation. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate room ventilation, if necessary with vapour extraction at the workplace.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep/Store only in original container. Provide for retaining containers, eg. floor pan without outflow.

Hints on joint storage

Store separately from foodstuffs.

Further information on storage conditions

Keep receptacles tightly sealed.

7.3. Specific end use(s)

Hardener (Crosslinker)

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to UK REACH Regulation

Hardener S

Revision date: 04.05.2022

Product code: 100140

Page 4 of 10

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
68512-30-1	Phenol, methylstyrenated			
Worker DNEL,		dermal		16,4 mg/kg bw/day
Worker DNEL,		inhalation		57 mg/m ³

PNEC values

CAS No	Substance	Environmental compartment	Value
25513-64-8	2,2,4-trimethylhexane-1,6-diamine	Freshwater	0,0295 mg/l
		Marine water	0,00295 mg/l
1477-55-0	1,3-Benzoldimethanamine	Freshwater	0,094 mg/l
		Marine water	0,0094 mg/l
68512-30-1	Phenol, methylstyrenated	Freshwater	0,014 mg/l
		Marine water	0,0014 mg/l
69-72-7	salicylic acid	Freshwater	0,2 mg/l
		Marine water	0,02 mg/l

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Protective goggles

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable material: NBR (Nitrile rubber) FKM (fluoro rubber) (Viton)

Thickness of the glove material: >= 0,5 mm

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Filter type: A-P2

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	light yellow
Odour:	Amines

Test method

Safety Data Sheet

according to UK REACH Regulation

Hardener S

Revision date: 04.05.2022

Product code: 100140

Page 5 of 10

pH-Value: not applicable

Changes in the physical state

Melting point/freezing point: not determined

Boiling point or initial boiling point and boiling range: > 200 °C

Flash point: > 100 °C

Flammability

Solid: not applicable

Gas: not applicable

Explosive properties

The product is: not explosive according to EU A.14

Lower explosion limits: 1,2 vol. %

Upper explosion limits: not determined

Auto-ignition temperature: 240 °C

Self-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C) 4 hPa

Density (at 23 °C): 1,038 g/cm³ ISO 2811-1

Water solubility: Immiscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Viscosity / dynamic: (at 25 °C) 240 mPa·s ISO 3219

Relative vapour density: not determined

Evaporation rate: not determined

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

no decomposition when stored and handled properly

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

The product does not contain any relevant quantities of substances with workplace-related limit values to be monitored.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

In case of fire may be liberated: toxic and caustic gases and vapours

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Harmful if swallowed.

ATEmix calculated

ATE (oral) 1597,6 mg/kg

Safety Data Sheet

according to UK REACH Regulation

Hardener S

Revision date: 04.05.2022

Product code: 100140

Page 6 of 10

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
61788-44-1	Phenol, styrenated				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
25513-64-8	2,2,4-trimethylhexane-1,6-diamine				
	oral	LD50 910 mg/kg	Rat		
1477-55-0	1,3-Benzoldimethanamine				
	oral	LD50 980 mg/kg	Rat		
	dermal	LD50 > 3100 mg/kg	Rat		
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			
68512-30-1	Phenol, methylstyrenated				
	oral	LD50 3600 mg/kg	Rabbit		
	dermal	LD50 2000 mg/kg	Rabbit		
69-72-7	salicylic acid				
	oral	LD50 891 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 2000 mg/kg	Rat	Manufacturer	
9046-10-0	Polyoxypropylenediamine				
	oral	LD50 475 mg/kg	Rat		
	dermal	LD50 2090 mg/kg	Rabbit		

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (Phenol, styrenated; 2,2,4-trimethylhexane-1,6-diamine; 1,3-Benzoldimethanamine; Phenol, methylstyrenated)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (salicylic acid)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to UK REACH Regulation

Hardener S

Revision date: 04.05.2022

Product code: 100140

Page 7 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
61788-44-1	Phenol, styrenated					
	Acute fish toxicity	LL50 14,8 mg/l	96 h	fish		
	Acute crustacea toxicity	EL50 1-10 mg/l	48 h	Daphnia magna		
25513-64-8	2,2,4-trimethylhexane-1,6-diamine					
	Acute algae toxicity	ErC50 29,5 mg/l	72 h	Desmodesmus subspicatus	IUCLID	
1477-55-0	1,3-Benzoldimethanamine					
	Acute fish toxicity	LC50 87,6 mg/l	96 h	Oryzias latipes (Ricefish)		
	Acute algae toxicity	ErC50 20,3 mg/l	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 15,2 mg/l	48 h	Daphnia magna		
68512-30-1	Phenol, methylstyrenated					
	Acute fish toxicity	LC50 25,8 mg/l	96 h			
	Acute algae toxicity	ErC50 15 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 14-51 mg/l	48 h	Daphnia magna		
69-72-7	salicylic acid					
	Acute fish toxicity	LC50 1370 mg/l	96 h	Pimephales promelas (fathead minnow)	Manufacturer	
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Scenedesmus subspicatus	Manufacturer	
	Acute crustacea toxicity	EC50 870 mg/l	48 h	Daphnia magna	Manufacturer	
9046-10-0	Polyoxypropylenediamine					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Piscis	Manufacturer	
	Acute algae toxicity	ErC50 135 mg/l	72 h	Scenedesmus sp.	Manufacturer	
	Acute crustacea toxicity	EC50 15 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
61788-44-1	Phenol, styrenated			
	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	73 %	14	
	Readily biodegradable (according to OECD criteria).			
25513-64-8	2,2,4-trimethylhexane-1,6-diamine			
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	7%	28	
	Not readily biodegradable (according to OECD criteria)			
1477-55-0	1,3-Benzoldimethanamine			
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	49 %	28	
	Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

The product has not been tested.

BCF

CAS No	Chemical name	BCF	Species	Source
61788-44-1	Phenol, styrenated	26,5	Carassius auratus (goldfish)	Quantitative structure-activity relationship (QSAR)

Safety Data Sheet

according to UK REACH Regulation

Hardener S

Revision date: 04.05.2022

Product code: 100140

Page 8 of 10

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

For disposal, comply with local regulations. Dispose of liquid component in a suitable incinerator. Product can be disposed of with household waste after curing.

List of Wastes Code - residues/unused products

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

Contaminated packaging

Dispose of waste according to applicable legislation

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number:**

UN 2735

14.2. UN proper shipping name:AMINES, LIQUID, CORROSIVE, N.O.S. (mphenylenebis(methylamine), Phenol, styrolisiert, 2,2,4-Trimethylhexane-1,6-diamine, Phenol, styrolized)
ENVIRONMENTALLY HAZARDOUS**14.3. Transport hazard class(es):**

8

14.4. Packing group:

II

Hazard label:

8



Classification code:

C7

Special Provisions:

274

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

80

Tunnel restriction code:

E

Inland waterways transport (ADN)**14.1. UN number:**

UN 2735

14.2. UN proper shipping name:AMINES, LIQUID, CORROSIVE, N.O.S. (mphenylenebis(methylamine), Phenol, styrolisiert, 2,2,4-Trimethylhexane-1,6-diamine, Phenol, styrolized)
ENVIRONMENTALLY HAZARDOUS**14.3. Transport hazard class(es):**

8

14.4. Packing group:

II

Hazard label:

8



Classification code:

C7

Special Provisions:

274

Limited quantity:

1 L

Excepted quantity:

E2

Marine transport (IMDG)**14.1. UN number:**

UN 2735

Safety Data Sheet

according to UK REACH Regulation

Hardener S

Revision date: 04.05.2022

Product code: 100140

Page 9 of 10

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-benzenedimethanamine, 2,2,4-trimethylhexane-1,6-diamine, phenol, styrolised) MARINE POLLUTANT

14.3. Transport hazard class(es): 8

14.4. Packing group: II

Hazard label: 8



Marine pollutant: Ja
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-A, S-B
 Segregation group: alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-benzenedimethanamine, 2,2,4-trimethylhexane-1,6-diamine, phenol, styrolised)

14.3. Transport hazard class(es): 8

14.4. Packing group: II

Hazard label: 8



Limited quantity Passenger: 0.5 L
 Passenger LQ: E2

IATA-packing instructions - Passenger: 1

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Phenol, styrolized

14.6. Special precautions for user

Warning: corrosive.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):
 Entry 3

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,14,15.

Abbreviations and acronyms

LP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level

Safety Data Sheet

according to UK REACH Regulation

Hardener S

Revision date: 04.05.2022

Product code: 100140

Page 10 of 10

PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Corr. 1A; H314	Manufacturer
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Repr. 2; H361d	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)