

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 28.10.2016
1.5	14.03.2017	1368065-00006	Date of first issue: 17.02.2015

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Product code : 000000000001907506

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Adhesive, binding agents

#### 1.3 Details of the supplier of the safety data sheet

Company : Suter Kunststoffe AG  
Aefligenstrasse 3  
CH-3312 Fraubrunnen

Telephone : +41 (0)31 763 60 60

E-mail address of person  
responsible for the SDS : info@swiss-composite.ch

#### 1.4 Emergency telephone number

Tox Info Suisse : Emergency number: 145

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008)**

Not a hazardous substance or mixture.

#### 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008)**

Not a hazardous substance or mixture.

Precautionary statements : **Prevention:**  
P271 Use only outdoors or in a well-ventilated area.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version 1.5      Revision Date: 14.03.2017      SDS Number: 1368065-00006      Date of last issue: 28.10.2016  
Date of first issue: 17.02.2015

### Additional Labelling

EUH210      Safety data sheet available on request.

### 2.3 Other hazards

Vapours may form explosive mixture with air.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature      :      Silicone elastomer

### Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Octamethylcyclotetrasiloxane	556-67-2 209-136-7 014-018-00-1 01-2119529238-36	Flam. Liq. 3; H226 Repr. 2; H361f Aquatic Chronic 4; H413	>= 0.25 - < 1

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice      :      In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders      :      First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled      :      If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact      :      In case of contact, immediately flush skin with soap and plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact      :      Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed      :      If swallowed, DO NOT induce vomiting.  
Get medical attention.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 28.10.2016
1.5	14.03.2017	1368065-00006	Date of first issue: 17.02.2015

Rinse mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Silicon oxides  
Formaldehyde

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice and personal protective equip-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 28.10.2016
1.5	14.03.2017	1368065-00006	Date of first issue: 17.02.2015

---

ment recommendations.

### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

Advice on safe handling : Avoid inhalation of vapour or mist.  
Do not swallow.  
Avoid contact with eyes.  
Avoid prolonged or repeated contact with skin.  
Handle in accordance with good industrial hygiene and safety practice.  
Keep container tightly closed.  
Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version 1.5      Revision Date: 14.03.2017      SDS Number: 1368065-00006      Date of last issue: 28.10.2016  
Date of first issue: 17.02.2015

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Advice on common storage : Do not store with the following product types:  
Strong oxidizing agents  
Explosives  
Gases

### 7.3 Specific end use(s)

Specific use(s) : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.  
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry ([www.SEHSC.com](http://www.SEHSC.com)) or contact the Dow Corning customer service group.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Amorphous fumed silica	112945-52-5	TWA (inhalable dust)	6 mg/m <sup>3</sup> (Silica)	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle.			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version 1.5      Revision Date: 14.03.2017      SDS Number: 1368065-00006      Date of last issue: 28.10.2016  
Date of first issue: 17.02.2015

	HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
		TWA (Respirable dust)	2.4 mg/m <sup>3</sup> (Silica)	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3. Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with. Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Octamethylcyclotetrasiloxane	556-67-2	TWA	10 ppm	US WEEL

**These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.**

Amorphous fumed silica

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Octamethylcyclotetrasiloxane	Workers	Inhalation	Acute systemic effects	73 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	73 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	73 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	73 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	13 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version 1.5      Revision Date: 14.03.2017      SDS Number: 1368065-00006      Date of last issue: 28.10.2016  
Date of first issue: 17.02.2015

	Consumers	Inhalation	Acute local effects	13 mg/m3
	Consumers	Inhalation	Long-term systemic effects	13 mg/m3
	Consumers	Inhalation	Long-term local effects	13 mg/m3
	Consumers	Ingestion	Acute systemic effects	3.7 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	3.7 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Octamethylcyclotetrasiloxane	Fresh water	0.00044 mg/l
	Marine water	0.000044 mg/l
	Fresh water sediment	0.64 mg/kg
	Marine sediment	0.064 mg/kg
	Soil	0.13 mg/kg
	Sewage treatment plant	> 10 mg/l

## 8.2 Exposure controls

### Engineering measures

Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

### Personal protective equipment

Eye protection : Wear the following personal protective equipment:  
Safety glasses

Hand protection  
Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
Flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 28.10.2016
1.5	14.03.2017	1368065-00006	Date of first issue: 17.02.2015

that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type (A)

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	:	viscous liquid
Colour	:	colourless
Odour	:	Acetic acid
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	> 100 °C
Flash point	:	87 °C Method: closed cup Other information: Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	1.03
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 28.10.2016
1.5	14.03.2017	1368065-00006	Date of first issue: 17.02.2015

---

Viscosity  
Viscosity, dynamic : 45,000 mPa.s

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Molecular weight : No data available

Particle size : Not applicable

Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Combustible liquid.  
Vapours may form explosive mixture with air.  
Use at elevated temperatures may form highly hazardous compounds.  
Can react with strong oxidizing agents.  
Acetic acid is formed upon contact with water or humid air.  
Hazardous decomposition products will be formed at elevated temperatures.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

Thermal decomposition : Formaldehyde

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version 1.5	Revision Date: 14.03.2017	SDS Number: 1368065-00006	Date of last issue: 28.10.2016 Date of first issue: 17.02.2015
----------------	------------------------------	------------------------------	---

Information on likely routes of exposure :

Inhalation  
Skin contact  
Ingestion  
Eye contact

### Acute toxicity

Not classified based on available information.

### Components:

#### Octamethylcyclotetrasiloxane:

Acute oral toxicity : LD50 (Rat): > 4,800 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: On basis of test data.

Acute inhalation toxicity : LC50 (Rat): 2975 ppm  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rabbit): > 2.5 ml/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: On basis of test data.

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### Octamethylcyclotetrasiloxane:

Species: Rabbit  
Result: No skin irritation  
Remarks: On basis of test data.

### Serious eye damage/eye irritation

Not classified based on available information.

### Components:

#### Octamethylcyclotetrasiloxane:

Species: Rabbit  
Result: No eye irritation  
Remarks: On basis of test data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version 1.5      Revision Date: 14.03.2017      SDS Number: 1368065-00006      Date of last issue: 28.10.2016  
Date of first issue: 17.02.2015

---

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### Octamethylcyclotetrasiloxane:

Assessment: Does not cause skin sensitisation.

Test Type: Maximisation Test

Species: Guinea pig

Result: negative

Remarks: On basis of test data.

### Germ cell mutagenicity

Not classified based on available information.

#### Components:

##### Octamethylcyclotetrasiloxane:

- Genotoxicity in vitro
- : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: On basis of test data.
  - : Test Type: Mutagenicity (in vitro mammalian cytogenetic test)  
Result: negative  
Remarks: On basis of test data.
  - : Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: On basis of test data.
  - : Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Result: negative  
Remarks: On basis of test data.
  - : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative  
Remarks: On basis of test data.
- Genotoxicity in vivo
- : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: On basis of test data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version 1.5      Revision Date: 14.03.2017      SDS Number: 1368065-00006      Date of last issue: 28.10.2016  
Date of first issue: 17.02.2015

---

Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: On basis of test data.

Germ cell mutagenicity- Assessment : Animal testing did not show any mutagenic effects.

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **Octamethylcyclotetrasiloxane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat, male and female  
Application Route: inhalation (vapour)  
Symptoms: Effects on fertility  
Remarks: On basis of test data.

Effects on foetal development : Test Type: Prenatal development toxicity study (teratogenicity)  
Species: Rabbit  
Application Route: inhalation (vapour)  
Symptoms: No effects on foetal development  
Remarks: On basis of test data.

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

### **STOT - single exposure**

Not classified based on available information.

### **STOT - repeated exposure**

Not classified based on available information.

### **Components:**

#### **Octamethylcyclotetrasiloxane:**

Exposure routes: Ingestion  
Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Exposure routes: inhalation (vapour)  
Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Exposure routes: Skin contact  
Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 28.10.2016
1.5	14.03.2017	1368065-00006	Date of first issue: 17.02.2015

---

### Repeated dose toxicity

#### Components:

##### **Octamethylcyclotetrasiloxane:**

Species: Rat  
Application Route: Ingestion  
Remarks: On basis of test data.

Species: Rat  
Application Route: inhalation (vapour)  
Remarks: On basis of test data.

Species: Rabbit  
Application Route: Skin contact  
Remarks: On basis of test data.

### Aspiration toxicity

Not classified based on available information.

#### Product:

No aspiration toxicity classification

### Further information

#### Components:

##### **Octamethylcyclotetrasiloxane:**

Remarks: Results from a 2 year repeated vapour inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **Octamethylcyclotetrasiloxane:**

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): > 0.0063 mg/l  
Exposure time: 336 h  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other : EC50 (Mysidopsis bahia (opossum shrimp)): > 0.0091 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version 1.5      Revision Date: 14.03.2017      SDS Number: 1368065-00006      Date of last issue: 28.10.2016  
Date of first issue: 17.02.2015

aquatic invertebrates      Exposure time: 96 h  
Remarks: No toxicity at the limit of solubility

Toxicity to algae      : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.022 mg/l  
Exposure time: 72 h  
Remarks: No toxicity at the limit of solubility

Toxicity to fish (Chronic toxicity)      : NOEC:  $\geq$  0.0044 mg/l  
Species: Oncorhynchus mykiss (rainbow trout)  
Remarks: On basis of test data.  
No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)      : NOEC:  $\geq$  0.0079 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Remarks: On basis of test data.  
No toxicity at the limit of solubility

### Ecotoxicology Assessment

Chronic aquatic toxicity      : May cause long lasting harmful effects to aquatic life.

## 12.2 Persistence and degradability

### Components:

#### Octamethylcyclotetrasiloxane:

Biodegradability      : Result: Not readily biodegradable.  
Biodegradation: 3.7 %  
Exposure time: 28 d  
Method: OECD Test Guideline 310

Stability in water      : Degradation half life: 69.3 - 144 h (24.6 °C)  
pH: 7 Method: OECD Test Guideline 111

## 12.3 Bioaccumulative potential

### Components:

#### Octamethylcyclotetrasiloxane:

Bioaccumulation      : Species: Pimephales promelas (fathead minnow)  
Bioconcentration factor (BCF): 12,400

Partition coefficient: n-octanol/water      : log Pow: 6.48 (25.1 °C)

## 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 28.10.2016
1.5	14.03.2017	1368065-00006	Date of first issue: 17.02.2015

### 12.5 Results of PBT and vPvB assessment

#### Components:

##### **Octamethylcyclotetrasiloxane:**

Assessment : Remarks: Octamethylcyclotetrasiloxane (D4) meets the current REACh Annex XIII criteria for PBT and vPvB. In Canada, D4 has been assessed and deemed to meet the PiT criteria. However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

### 12.6 Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

## SECTION 14: Transport information

### 14.1 UN number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 28.10.2016
1.5	14.03.2017	1368065-00006	Date of first issue: 17.02.2015

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Dimethylbis[(1-oxoneodecyl)oxy]stannane (20)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

#### The components of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

REACH : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 28.10.2016
1.5	14.03.2017	1368065-00006	Date of first issue: 17.02.2015

- ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from inventory listing.
- KECI : All ingredients listed, exempt or notified.
- PICCS : All ingredients listed or exempt.
- DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
- TCSI : All ingredients listed or exempt.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

#### Full text of H-Statements

- H226 : Flammable liquid and vapour.
- H361f : Suspected of damaging fertility.
- H413 : May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations

- Aquatic Chronic : Chronic aquatic toxicity
- Flam. Liq. : Flammable liquids
- Repr. : Reproductive toxicity
- GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
- US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
- GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
- US WEEL / TWA : Time weighted average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**DOW CORNING**

## DOW CORNING(R) 734 FLOWABLE SEALANT CLEAR

Version	Revision Date:	SDS Number:	Date of last issue: 28.10.2016
1.5	14.03.2017	1368065-00006	Date of first issue: 17.02.2015

---

to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN