



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SD 228
Product code : 1991.
HARDENER
UFI : T0H5-C0Y0-Y007-U0T2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Hardener
Uses advised against : data not available

1.3. Details of the supplier of the safety data sheet

Registered company name : Suter Kunststoffe AG
Address : Aefligenstrasse 3, CH-3312 Fraubrunnen
Telephone : +41 (0)31 763 60 60 Fax : +41 (0)31 763 60 61
info@swiss-composite.ch
Site web : <http://www.swiss-composite.ch>

1.4. Emergency telephone number : .

ToxInfo Suisse, Tel 145 (Int. +41 44 251 51 51)

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).
Skin corrosion, Category 1A (Skin Corr. 1A, H314).
Serious eye damage, Category 1 (Eye Dam. 1, H318).
Skin sensitisation, Category 1A (Skin Sens. 1A, H317).
Reproductive toxicity, Category 1A (Repr. 1A, H360FD).
Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).
This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07

GHS05

GHS09

GHS08

Signal Word :

DANGER

Product identifiers :

EC 203-615-4

MELAMINE

EC 500-105-6

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA

612-067-00-9

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

EC 219-941-5 1,3-CYCLOHEXANEDIMETHANAMINE

EC 266-047-6 FRITS, CHEMICALS

Additional labeling :

For professional users only.

Hazard statements :

H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H360FD May damage fertility. May damage the unborn child.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P202 Do not handle until all safety precautions have been read and understood.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/

...

Precautionary statements - Response :

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor/...
 P363 Wash contaminated clothing before reuse.
 P391 Collect spillage.

2.3. Other hazards

The mixture contains substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annex XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	Classification (EC) 1272/2008	Note	%
CAS: 108-78-1 EC: 203-615-4 REACH: 01-2119485947-16-XXXX MELAMINE	GHS08 Wng Repr. 2, H361f	[2] [6]	25 \leq x % < 50
CAS: 39423-51-3 EC: 500-105-6 REACH: 01-2119556886-20-XXXX PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 2, H411		10 \leq x % < 25
INDEX: 612-067-00-9 CAS: 2855-13-2 EC: 220-666-8 REACH: 01-2119514687-32-XXXX 3-AMINOMETHYL-3,5,5-TRIMETHYLCY CLOHEXYLAMINE	GHS05, GHS07 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317		2.5 \leq x % < 10
CAS: 2579-20-6 EC: 219-941-5 REACH: 01-2119543741-41-XXXX 1,3-CYCLOHEXANEDIMETHANAMINE	GHS07, GHS05 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412		2.5 \leq x % < 10

CAS: 13463-67-7 EC: 236-675-5 REACH: 01-2119489379-17-XXXX TITANIUM DIOXIDE (IN THE FORM OF A POWDER CONTAINING NOT 1 % OR MORE PARTICLES OF A DIAMETER <= 10 µM)		[1]	2.5 <= x % < 10
CAS: 65997-18-4 EC: 266-047-6 REACH: 01-2119548361-42-XXXX FRITS, CHEMICALS	GHS08, GHS09 Dgr Repr. 1A, H360FD Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1	[2] [XVII]	2.5 <= x % < 10
CAS: 770-35-4 EC: 212-222-7 REACH: 01-2119486566-23-XXXX 1-PHENOXYPROPAN-2-OL	GHS05 Dgr Eye Dam. 1, H318		2.5 <= x % < 10
CAS: 69-72-7 EC: 200-712-3 REACH: 01-2119486984-17-XXXX SALICYLIC ACID	GHS07, GHS05, GHS08 Dgr Acute Tox. 4, H302 Eye Dam. 1, H318 Repr. 2, H361d	[2]	1 <= x % < 2.5

Specific concentration limits:

Identification	Specific concentration limits	ATE
CAS: 108-78-1 EC: 203-615-4 REACH: 01-2119485947-16-XXXX MELAMINE		inhalation: ATE = 5190 mg/l 4h (dust/mist) dermal: ATE = 1000 mg/kg BW oral: ATE = 3000 mg/kg BW
CAS: 39423-51-3 EC: 500-105-6 REACH: 01-2119556886-20-XXXX PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA		oral: ATE = 550 mg/kg BW
INDEX: 612-067-00-9 CAS: 2855-13-2 EC: 220-666-8 REACH: 01-2119514687-32-XXXX 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE	Skin Sens. 1A: H317 C>= 0.001%	oral: ATE = 1030 mg/kg BW
CAS: 2579-20-6 EC: 219-941-5 REACH: 01-2119543741-41-XXXX 1,3-CYCLOHEXANEDIMETHANAMINE		dermal: ATE = 1700 mg/kg BW oral: ATE = 880 mg/kg BW
CAS: 69-72-7 EC: 200-712-3 REACH: 01-2119486984-17-XXXX SALICYLIC ACID		oral: ATE = 891 mg/kg BW

Information on ingredients :

(Full text of H-phrases: see section 16)

[XVII] Restricted substance under Regulation (EC) No. 1907/2006 (REACH), Annex XVII.

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

[6] Substances of very high concern (SVHC).

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

If inhaled, move the patient to fresh air and keep warm and rest.

Never give anything by mouth. If unconscious, place in recovery position and call an ambulance.

Consult a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

Flush with large amounts of water. Remove contact lenses if the victim is. Continue to rinse. Seek medical attention if symptoms persist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor :

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to remain under medical supervision for 48 hours.

Contact a specialist for treatment poisoning if large quantities have been ingested or inhaled.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- powder

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- nitrogen oxide (NO)
- nitrogen dioxide (NO₂)

5.3. Advice for firefighters

Firefighters should wear suitable protective clothing and a respirator mask with self- full operated in positive pressure mode.

Wear conform with the European standard EN 469.

SECTION 6 : ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

Avoid exposure to pregnant women and warn women of child-bearing age of the possible risks

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid exposure - obtain special instructions before use.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep away from food and drink, including those for animals.

Store in original container protected from direct sunlight in a dry, cool and well ventilated area away from heat sources.

Keep container tightly closed in a dry place.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

Scope advised: Fire

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
13463-67-7	10 mg/m3			A4	

- China (GBZ 2.1, 2007) :

CAS	TWA :	STEL :	Anm :	TWA :	STEL :	Anm :
13463-67-7	8 mg/m3					

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
13463-67-7	-	10	-	-	-	-

- Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT), 2019) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :

13463-67-7	10 mg/m3				
- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :					
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
13463-67-7	4 mg/m3				

Derived no effect level (DNEL) or derived minimum effect level (DMEL):**SALICYLIC ACID (CAS: 69-72-7)****Final use:**

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
2 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
12 mg of substance/m3

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term local effects.
5 mg of substance/m3

Final use:

Exposure method:
Potential health effects:
DNEL :

Man exposed via the environment.

Ingestion.
Short term systemic effects.
4 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Ingestion.
Long term systemic effects.
1 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Dermal contact.
Long term systemic effects.
1 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
4 mg of substance/m3

1-PHENOXYPROPAN-2-OL (CAS: 770-35-4)**Final use:**

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
42 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
25.7 mg of substance/m3

Final use:

Exposure method:
Potential health effects:
DNEL :

Consumers.

Ingestion.
Long term systemic effects.
3.65 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Dermal contact.
Long term systemic effects.
21 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
12.7 mg of substance/m3

TITANIUM DIOXIDE (IN THE FORM OF A POWDER CONTAINING NOT 1 % OR MORE PARTICLES OF A DIAMETER <= 10 µM) (CAS: 13463-67-7)**Final use:**

Exposure method:
Potential health effects:

Workers.

Inhalation.
Long term local effects.

DNEL : 10 mg of substance/m3

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 0.8 mg of substance/m3

Final use:**Consumers.**

Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 700 mg/kg body weight/day

1,3-CYCLOHEXANEDIMETHANAMINE (CAS: 2579-20-6)

Final use:**Workers.**

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 0.1 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 0.00947 mg of substance/m3

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Final use:**Workers.**

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 4 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 4.9 mg of substance/m3

Final use:**Consumers.**

Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 0.5 mg/kg body weight/day

MELAMINE (CAS: 108-78-1)

Final use:**Workers.**

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 11.8 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Short term systemic effects.
DNEL : 117 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 8.3 mg of substance/m3

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 82.3 mg of substance/m3

Final use:**Consumers.**

Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 0.42 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 4.2 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.
DNEL : 1.5 mg of substance/m3

Predicted no effect concentration (PNEC):

SALICYLIC ACID (CAS: 69-72-7)

Environmental compartment: Soil.
PNEC : 0.17 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.2 mg/l

Environmental compartment: Sea water.
PNEC : 0.02 mg/l

Environmental compartment: Fresh water sediment.
PNEC : 1.42 mg/kg

Environmental compartment: Marine sediment.
PNEC : 0.14 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 162 mg/l

1-PHENOXYPROPAN-2-OL (CAS: 770-35-4)

Environmental compartment: Soil.
PNEC : 0.02 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.1 mg/l

Environmental compartment: Sea water.
PNEC : 0.01 mg/l

Environmental compartment: Intermittent waste water.
PNEC : 1 mg/l

Environmental compartment: Fresh water sediment.
PNEC : 0.38 mg/kg

Environmental compartment: Marine sediment.
PNEC : 0.038 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 10 mg/l

TITANIUM DIOXIDE (IN THE FORM OF A POWDER CONTAINING NOT 1 % OR MORE PARTICLES OF A DIAMETER <= 10 µM) (CAS: 13463-67-7)

Environmental compartment: Soil.
PNEC : 100 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.184 mg/l

Environmental compartment: Sea water.
PNEC : 0.0184 mg/l

Environmental compartment: Intermittent waste water.
PNEC : 0.61 mg/l

Environmental compartment: Fresh water sediment.
PNEC : 1000 mg/kg

Environmental compartment: Marine sediment.
PNEC : 100 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 100 mg/l

1,3-CYCLOHEXANEDIMETHANAMINE (CAS: 2579-20-6)
Environmental compartment: Soil.
PNEC : 0.024 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.033 mg/l

Environmental compartment: Sea water.
PNEC : 0.003 mg/l

Environmental compartment: Fresh water sediment.
PNEC : 0.218 mg/kg

Environmental compartment: Marine sediment.
PNEC : 0.022 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 10 mg/l

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)
Environmental compartment: Soil.
PNEC : 0.002 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.004 mg/l

Environmental compartment: Sea water.
PNEC : 0.00044 mg/l

Environmental compartment: Intermittent waste water.
PNEC : 0.044 mg/l

Environmental compartment: Fresh water sediment.
PNEC : 0.0224 mg/kg

Environmental compartment: Marine sediment.
PNEC : 0.00224 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 10 mg/l

MELAMINE (CAS: 108-78-1)
Environmental compartment: Soil.
PNEC : 0.206 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.51 mg/l

Environmental compartment: Sea water.
PNEC : 0.051 mg/l

Environmental compartment: Intermittent waste water.
PNEC : 2 mg/l

Environmental compartment: Fresh water sediment.
PNEC : 2.524 mg/kg

Environmental compartment: Marine sediment.
PNEC : 0.252 mg/kg

Environmental compartment:
PNEC :

Waste water treatment plant.
200 mg/l

8.2. Exposure controls

Use only with adequate ventilation or provided with ventilation at the source.

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Butyl Rubber (Isobutylene-isoprene copolymer)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

Mask with filter type A, B, E, K, P

Attention! If the protection group is insufficient.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state :	Viscous liquid.
aspect :	gel

Colour

Color :	white
---------	-------

Odour

Odour threshold :	Not stated.
-------------------	-------------

Melting point

Melting point/melting range :	Not relevant.
-------------------------------	---------------

Freezing point

Freezing point / Freezing range :	Not stated.
-----------------------------------	-------------

Boiling point or initial boiling point and boiling range

Boiling point/boiling range :	Not relevant.
Flammability	
Flammability (solid, gas) :	Not stated.
Lower and upper explosion limit	
Explosive properties, lower explosivity limit (%) :	Not stated.
Explosive properties, upper explosivity limit (%) :	Not stated.
Flash point	
Flash Point Interval :	FP > 100°C.
Auto-ignition temperature	
Self-ignition temperature :	Not relevant.
Decomposition temperature	
Decomposition point/decomposition range :	Not relevant.
pH	
pH (aqueous solution) :	Not stated.
pH :	Not relevant.
Kinematic viscosity	
Viscosity :	4 690 ± 1 540 mPa.s @ 25°C
Solubility	
Water solubility :	Insoluble.
Fat solubility :	Not stated.
Partition coefficient n-octanol/water (log value)	
Partition coefficient: n-octanol/water :	Not stated.
Vapour pressure	
Vapour pressure (50°C) :	Not relevant.
Density and/or relative density	
Density :	1.41 ± 0.03 @ 20°C
Relative vapour density	
Vapour density :	Not stated.

Particle characteristics

The mixture does not contain nanoforms.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- humidity
- contact with air

10.5. Incompatible materials

Keep away from :

- strong oxidising agents

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- nitrogen oxide (NO)
- nitrogen dioxide (NO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Harmful if swallowed.

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

May cause an allergic reaction by skin contact.

Known human reproductive toxicant.

May damage fertility and the unborn child.

11.1.1. Substances**Acute toxicity :**

SALICYLIC ACID (CAS: 69-72-7)

Oral route : LD50 = 891 mg/kg bodyweight/day
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 2000 mg/kg bodyweight/day
Species : Rat
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Dusts/mist) : LC50 > 0.9 mg/l
Species : Rat

1-PHENOXYPROPAN-2-OL (CAS: 770-35-4)

Oral route : LD50 > 2000 mg/kg bodyweight/day
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 2000 mg/kg bodyweight/day
Species : Rat
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Dusts/mist) : LC50 > 5 mg/l
Species : Rat
OECD Guideline 403 (Acute Inhalation Toxicity)

TITANIUM DIOXIDE (IN THE FORM OF A POWDER CONTAINING NOT 1 % OR MORE PARTICLES OF A DIAMETER <= 10 µM) (CAS: 13463-67-7)

Oral route : LD50 > 5000 mg/kg bodyweight/day
Species : Rat
OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

Dermal route : LD50 > 10000 mg/kg bodyweight/day
Species : Rat

Inhalation route (Dusts/mist) : LC50 > 6.82 mg/l
Species : Rat
Duration of exposure : 4 h

1,3-CYCLOHEXANEDIMETHANAMINE (CAS: 2579-20-6)

Oral route : LD50 = 880 mg/kg bodyweight/day
Species : Rat

Dermal route : LD50 = 1700 mg/kg bodyweight/day
Species : Rabbit

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE (CAS: 2855-13-2)

Oral route : LD50 = 1030 mg/kg bodyweight/day

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Oral route : LD50 = 550 mg/kg bodyweight/day

Species : Rat
OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

Dermal route :
LD50 > 1000 mg/kg bodyweight/day
Species : Rat
OECD Guideline 402 (Acute Dermal Toxicity)

MELAMINE (CAS: 108-78-1)
Oral route :
LD50 = 3000 mg/kg bodyweight/day
Species : Rat

Dermal route :
LD50 = 1000 mg/kg bodyweight/day
Species : Rabbit

Inhalation route (Dusts/mist) :
LC50 = 5190 mg/l
Duration of exposure : 4 h

Skin corrosion/skin irritation :

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)
Species : Rabbit
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Species : Rabbit
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Respiratory or skin sensitisation :

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)
Guinea Pig Maximisation Test (GMPT) :
Non-sensitiser.
Species : Guinea pig
OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity :

1,3-CYCLOHEXANEDIMETHANAMINE (CAS: 2579-20-6)
Ames test (in vitro) :
Negative.

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)
Mutagenesis (in vivo) :
Negative.
Species : Mouse
OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Ames test (in vitro) :
Negative.
With or without metabolic activation.

Reproductive toxicant :

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)
No toxic effect for reproduction
Study on fertility :
Species : Rat
OECD Guideline 414 (Prenatal Developmental Toxicity Study)
Study on development :
Species : Rat
OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

MELAMINE (CAS: 108-78-1)
Suspected of damaging fertility.

Specific target organ systemic toxicity - repeated exposure :

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)
Oral route :
C >= 100 mg/kg bodyweight/day
Species : Rat
Duration of exposure : 90 days
OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Dermal route : C >= 160 mg/kg bodyweight/day
Species : Rat
Duration of exposure : 90 days
OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

11.1.2. Mixture

No toxicological data available for the mixture.

11.2. Information on other hazards

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 13463-67-7 : IARC Group 2B : The agent is possibly carcinogenic to humans.

CAS 108-78-1 : IARC Group 2B : The agent is possibly carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

1-PHENOXYPROPAN-2-OL (CAS: 770-35-4)

Fish toxicity : LC50 > 100 mg/l
Duration of exposure : 96 h
OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity : EC50 > 100 mg/l
Species : Daphnia magna
Duration of exposure : 48 h
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity : ECr50 > 100 mg/l
Species : Scenedesmus subspicatus
Duration of exposure : 72 h
Autres lignes directrices

Aquatic plant toxicity : ECr50 > 100 mg/l
Duration of exposure : 72 h

TITANIUM DIOXIDE (IN THE FORM OF A POWDER CONTAINING NOT 1 % OR MORE PARTICLES OF A DIAMETER <= 10 µM) (CAS: 13463-67-7)

Fish toxicity : LC50 = 1000 mg/l
Species : Leuciscus idus
Duration of exposure : 48 h

Crustacean toxicity : EC50 > 100 mg/l
Species : Daphnia magna
Duration of exposure : 48 h
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity : ECr50 > 100 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h

NOEC = 1 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h

1,3-CYCLOHEXANEDIMETHANAMINE (CAS: 2579-20-6)

Fish toxicity : LC50 = 130 mg/l
Species : Leuciscus idus
Duration of exposure : 96 h
OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity : EC50 = 65.4 mg/l

Species : Daphnia magna
Duration of exposure : 48 h
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity :
ECr50 = 58.4 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h
OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

NOEC = 14.4 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h
OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Fish toxicity :
LC50 > 100 mg/l
Species : Oncorhynchus mykiss
Duration of exposure : 96 h
OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity :
EC50 = 13 mg/l
Species : Daphnia magna
Duration of exposure : 48 h
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity :
ECr50 = 4.4 mg/l
Species : Selenastrum capricornutum
Duration of exposure : 72 h
OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

MELAMINE (CAS: 108-78-1)

Fish toxicity :
LC50 > 3000 mg/l
Species : Oncorhynchus mykiss
Duration of exposure : 96 h

Crustacean toxicity :
EC50 > 2000 mg/l
Species : Daphnia magna
Duration of exposure : 48 h

Algae toxicity :
ECr50 = 325 mg/l
Duration of exposure : 96 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

1-PHENOXYPROPAN-2-OL (CAS: 770-35-4)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

TITANIUM DIOXIDE (IN THE FORM OF A POWDER CONTAINING NOT 1 % OR MORE PARTICLES OF A DIAMETER <= 10 µM) (CAS: 13463-67-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

1,3-CYCLOHEXANEDIMETHANAMINE (CAS: 2579-20-6)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Biodegradability : Non-rapidly degradable.

MELAMINE (CAS: 108-78-1)

Biodegradability : no degradability data is available, the substance is considered as not

degrading quickly.

12.3. Bioaccumulative potential

12.3.1. Substances

1-PHENOXYPROPAN-2-OL (CAS: 770-35-4)

Octanol/water partition coefficient : log K_{ow} = 1.41

Bioaccumulation : BCF < 100

1,3-CYCLOHEXANEDIMETHANAMINE (CAS: 2579-20-6)

Octanol/water partition coefficient : log K_{ow} = 0.783

OCDE Ligne directrice 107 (Coefficient de partage (n-octanol/eau): méthode par agitation en flacon)

PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA (CAS: 39423-51-3)

Octanol/water partition coefficient : log K_{ow} = -1.13

MELAMINE (CAS: 108-78-1)

Octanol/water partition coefficient : log K_{ow} = -1.14

Bioaccumulation : BCF < 3.8

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 2 : Hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

07 01 08 * other still bottoms and reaction residues

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2022 [41-22] - ICAO/IATA 2023 [64]).

14.1. UN number or ID number

2735

14.2. UN proper shipping name

UN2735=POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(propylidynetrimethanol, propoxylated, reaction products with ammonia, 1,3-cyclohexanedimethanamine)

14.3. Transport hazard class(es)

- Classification :



8

14.4. Packing group

II

14.5. Environmental hazards

- Environmentally hazardous material :

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C7	II	8	80	1 L	274	E2	2	E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	8	-	II	1 L	F-A, S-B	274	E2	Category A	SGG18 SG35	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	8	-	II	851	1 L	855	30 L	A3 A803	E2	
	8	-	II	Y840	0.5 L	-	-	A3 A803	E2	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

Marine pollutant (IMDG 3.1.2.9):(frits, chemicals)

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

Container information:

No data available.

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture contains at least one restricted substance under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):

<https://echa.europa.eu/substances-restricted-under-reach>. Please refer to Section 3 to identify the substance involved.

For professional users only.

Explosives precursors :

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

Particular provisions :

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBWs) :

WGK 2 : Hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a

guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H360FD	May damage fertility. May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.
LC50 : The concentration of a test substance resulting in 50% lethality in a given period.
EC50 : The effective concentration of substance that causes 50% of the maximum response.
ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.
NOEC : The concentration with no observed effect.
REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.
ATE : Acute Toxicity Estimate
BW : Body Weight
DNEL : Derived No-Effect Level
PNEC : Predicted No-Effect Concentration
CMR: Carcinogenic, mutagenic or reprotoxic.
UFI : Unique formulation identifier.
STEL : Short-term exposure limit
TWA : Time Weighted Averages
TMP : French Occupational Illness table
TLV : Threshold Limit Value (exposure)
AEV : Average Exposure Value.
ADR : European agreement concerning the international carriage of dangerous goods by Road.
IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.
WGK : Wassergefährdungsklasse (Water Hazard Class).
GHS05 : Corrosion
GHS07 : Exclamation mark
GHS08 : Health hazard
GHS09 : Environment
PBT: Persistent, bioaccumulable and toxic.
vPvB : Very persistent, very bioaccumulable.
SVHC : Substances of very high concern.