

1 Identification

- **Product identifier**
- **Trade name:** *XTEND CX-501*
- **Application of the substance / the mixture** *Industrial cleaner*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Suter Kunststoffe AG
Aefligenstrasse 3
CH-3312 Fraubrunnen
info@swiss-composite.ch
- **Information department:** *Product safety department*
- **Emergency telephone number:**
 .
Tox-Info-Suisse Tel. Nr. 145 (24 hours)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

toluene

butanone

- **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/11/2015

Reviewed on 12/11/2015

Trade name: XTEND CX-501

(Contd. of page 1)

*May cause drowsiness or dizziness.**May cause damage to organs through prolonged or repeated exposure.**May be fatal if swallowed and enters airways.***· Precautionary statements***Keep away from heat/sparks/open flames/hot surfaces. No smoking.**Use explosion-proof electrical/ventilating/lighting/equipment.**Do not breathe dust/fume/gas/mist/vapors/spray.**Wear protective gloves / eye protection / face protection.**Ground/bond container and receiving equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Wash thoroughly after handling.**Use only outdoors or in a well-ventilated area.**Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**IF SWALLOWED: Immediately call a POISON CENTER/ doctor.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.**Continue rinsing.**Specific treatment (see on this label).**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**Call a POISON CENTER/doctor if you feel unwell.**IF exposed or concerned: Get medical advice/attention.**If skin irritation occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**Get medical advice/attention if you feel unwell.**Do NOT induce vomiting.**In case of fire: Use for extinction: CO₂, powder or water spray.**Take off contaminated clothing and wash it before reuse.**Store locked up.**Store in a well-ventilated place. Keep container tightly closed.**Store in a well-ventilated place. Keep cool.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· Classification system:****· NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH *2 Health = *2

FIRE 3 Fire = 3

REACTIVITY 0 Reactivity = 0

· Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures**· Description:** Mixture of the substances listed below with nonhazardous additions.**· Dangerous components:**

108-88-3 toluene

25-50%

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/11/2015

Reviewed on 12/11/2015

Trade name: XTEND CX-501

(Contd. of page 2)

78-93-3 butanone

25-50%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Store in cool, dry place in tightly closed receptacles.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/11/2015

Reviewed on 12/11/2015

Trade name: XTEND CX-501

(Contd. of page 3)

- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI

78-93-3 butanone

PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI

· Ingredients with biological limit values:

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/11/2015

Reviewed on 12/11/2015

Trade name: XTEND CX-501

(Contd. of page 4)

BEI 2 mg/L
 Medium: urine
 Time: end of shift
 Parameter: MEK

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Color: Clear

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/11/2015

Reviewed on 12/11/2015

Trade name: XTEND CX-501

(Contd. of page 5)

Boiling point/Boiling range:	80 - 140 C
· Flash point:	< 23 °C (< 73 °F)
· Flammability (solid, gaseous):	Not applicable.
· Percentage Volatile	100 %
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	105 hPa (79 mm Hg)
· Density:	Not determined.
· Relative density	0.842
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	< 15 cps @ 25C
· Dynamic:	Not determined.
· Kinematic:	Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** The product is stable under recommended storage conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

78-93-3 butanone

Oral	LD50	3300 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/11/2015

Reviewed on 12/11/2015

Trade name: XTEND CX-501

(Contd. of page 6)

- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

108-88-3 | toluene

3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1993
- **UN proper shipping name**
- **DOT** Flammable liquids, n.o.s. (Toluene, Ethyl methyl ketone)
- **IMDG** FLAMMABLE LIQUID, N.O.S. (TOLUENE, ETHYL METHYL KETONE (METHYL ETHYL KETONE))
- **IATA** Flammable liquid, n.o.s. (Toluene, Ethyl methyl ketone)

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/11/2015

Reviewed on 12/11/2015

Trade name: XTEND CX-501

(Contd. of page 7)

· Transport hazard class(es)	
· DOT, IMDG, IATA	
· Class	3 Flammable liquids
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	F-E,S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (TOLUENE, ETHYL METHYL KETONE), 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 313 (Specific toxic chemical listings):**

All ingredients are listed.

- **TSCA (Toxic Substances Control Act) (Substances not listed):**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

108-88-3 | toluene

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

108-88-3 | toluene

- **US State Regulations**

- **Connecticut - Hazardous Air Pollutants - HLVs (30 min)**

None of the ingredients is listed.

- **Connecticut - Hazardous Air Pollutants - HLVs (8 hr)**

None of the ingredients is listed.

- **Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)**

None of the ingredients is listed.

- **Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations**

None of the ingredients is listed.

- **Occupational Exposure Limits - TWAs**

None of the ingredients is listed.

- **Michigan - Occupational Exposure Limits - Skin Designations**

None of the ingredients is listed.

- **Michigan - Occupational Exposure Limits - TWAs**

None of the ingredients is listed.

- **Minnesota - Hazardous Substance List**

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/11/2015

Reviewed on 12/11/2015

Trade name: XTEND CX-501

(Contd. of page 8)

· Minnesota - Permissible Exposure Limits - Skin Designations

None of the ingredients is listed.

· Minnesota - Permissible Exposure Limits - TWAs

None of the ingredients is listed.

· New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour

None of the ingredients is listed.

· New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual

None of the ingredients is listed.

· New York - Occupational Exposure Limits - Skin Designations

None of the ingredients is listed.

· New York - Occupational Exposure Limits - TWAs

None of the ingredients is listed.

· North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour

None of the ingredients is listed.

· North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour

None of the ingredients is listed.

· Oregon - Permissible Exposure Limits - TWAs

None of the ingredients is listed.

· Tennessee - Occupational Exposure Limits - Skin Designations

None of the ingredients is listed.

· Tennessee - Occupational Exposure Limits - TWAs

None of the ingredients is listed.

· Texas - Effects Screening Levels - Long Term

None of the ingredients is listed.

· Texas - Effects Screening Levels - Short Term

None of the ingredients is listed.

· Vermont - Permissible Exposure Limits - Skin Designations

None of the ingredients is listed.

· Vermont - Permissible Exposure Limits - TWAs

None of the ingredients is listed.

· Washington - Permissible Exposure Limits - Skin Designations

None of the ingredients is listed.

· Washington - Permissible Exposure Limits - STELs

None of the ingredients is listed.

· Washington - Permissible Exposure Limits - TWAs

None of the ingredients is listed.

· Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet

None of the ingredients is listed.

· Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet

None of the ingredients is listed.

· Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/11/2015

Reviewed on 12/11/2015

Trade name: XTEND CX-501

(Contd. of page 9)

· **Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II
78-93-3	butanone	I

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

toluene
butanone

· **Hazard statements**

Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves / eye protection / face protection.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see on this label).
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.
IF exposed or concerned: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Get medical advice/attention if you feel unwell.
Do NOT induce vomiting.
In case of fire: Use for extinction: CO2, powder or water spray.

(Contd. on page 11)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/11/2015

Reviewed on 12/11/2015

Trade name: XTEND CX-501

(Contd. of page 10)

Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **National regulations:**

The components of this product are listed on the USA (TSCA) inventory.
 The components of this product are listed on the Canadian (DSL) inventory.
 The components of this product are listed on the European (EINECS) inventory.
 The components of this product are listed on the Australia (AICS) inventory.
 The components of this product are listed on the Japan (ENCS) inventory.
 The components of this product are listed on the South Korean (KECI) inventory.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer: This data is offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review recommendations in the specific context of the intended use and determine whether they are appropriate.

• **Contact:** info@axelplastics.com

• **Date of preparation / last revision** 12/11/2015 / 1

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

• *** Data compared to the previous version altered.**