

REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

Skin corrosion, Category 1A	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 1B	H360F: May damage fertility.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2, Pancreas, Liver, Kidney	H373: May cause damage to organs through prolonged or repeated exposure if swallowed.
Acute aquatic toxicity, Category 1	H400: Very toxic to aquatic life.
Chronic aquatic toxicity, Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 + H312 Harmful if swallowed or in contact with skin
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.
 H360F May damage fertility.
 H373 May cause damage to organs (Pancreas, Liver, Kidney) through prolonged or repeated exposure if swallowed.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
 P201 Obtain special instructions before use.
 P260 Do not breathe mist or vapours.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON

REN HY 5212

Version 1.0 Revision Date: 06.04.2017 SDS Number: 400001009577 Date of last issue: -
Date of first issue: 06.04.2017

P305 + P351 + P338 + P310 CENTER/doctor.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Hazardous components which must be listed on the label:

2,4-diamino-3,5-diethyltoluene

cyclohex-1,2-ylenediamine

bisphenol A

Additional Labelling:

Restricted to professional users.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Diethylmethylbenzenediamine	68479-98-1 270-877-4 612-130-00-0 01-2119486805-25	Acute Tox. 4; H302 Acute Tox. 4; H312 Eye Irrit. 2; H319 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	60 - 100
Cyclohex-1,2-ylenediamine	694-83-7 211-776-7 -	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Corr. 1A; H314 STOT SE 3; H335	13 - 30
4,4'-Isopropylidenediphenol	80-05-7 201-245-8 604-030-00-0 01-2119457856-23	Eye Dam. 1; H318 Skin Sens. 1; H317 Repr. 1B; H360F STOT SE 3; H335 Aquatic Chronic 2; H411	7 - 13
Toluene-4-sulphonic acid	104-15-4	STOT SE 3; H335	1 - 3

REN HY 5212

Version 1.0 Revision Date: 06.04.2017 SDS Number: 400001009577 Date of last issue: -
Date of first issue: 06.04.2017

	203-180-0 -	Skin Irrit. 2; H315 Eye Irrit. 2; H319	
--	----------------	---	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : High volume water jet

REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : No data is available on the product itself.
- Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- No data is available on the product itself.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Specific extinguishing methods : No data is available on the product itself.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol.

REN HY 5212

Version Revision Date: SDS Number: Date of last issue: -
1.0 06.04.2017 400001009577 Date of first issue: 06.04.2017

Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Storage class (TRGS 510) : 6.1C, Combustible, acute toxic Cat.3 / toxic compounds or compounds which causing chronic effects

Recommended storage temperature : 2 - 40 °C

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
bisphenol A	80-05-7	AGW (Inhalable fraction)	5 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	1;(I)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), When there is			

REN HY 5212

Version 1.0 Revision Date: 06.04.2017 SDS Number: 400001009577 Date of last issue: -
Date of first issue: 06.04.2017

	compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
		TWA (inhalable dust)	10 mg/m ³
Further information	Indicative		

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)

Material : Nitrile rubber
Break through time : 10 - 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : yellow
Odour : slight
Odour Threshold : No data is available on the product itself.
pH : No data is available on the product itself.
Freezing point : No data is available on the product itself.
Melting point : No data is available on the product itself.
Boiling point : No data is available on the product itself.

REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

Flash point : > 150 °C
Method: Pensky-Martens closed cup, closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Burning rate : No data is available on the product itself.

Upper explosion limit : No data is available on the product itself.

Lower explosion limit : No data is available on the product itself.

Vapour pressure : < 0,1 hPa (25 °C)

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

Density : 1 g/cm³ (20 °C)

Solubility(ies)
Water solubility : partly soluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C

Viscosity
Viscosity, dynamic : 250 - 350 mPa.s (25 °C)

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

toluene-4-sulphonic acid:
Species: Rabbit
Method: OECD Test Guideline 404
Result: Irritating to skin.

Serious eye damage/eye irritation

Components:

diethylmethylbenzenediamine:
Species: Rabbit
Assessment: Irritant
Result: Irritating to eyes.

Species: Rabbit
Assessment: Irritant
Method: OECD Test Guideline 405
Result: Normally reversible injuries

cyclohex-1,2-ylenediamine:
Species: Rabbit
Result: Risk of serious damage to eyes.
GLP: no

bisphenol A:
Species: Rabbit
Method: OECD Test Guideline 405
Result: Irreversible effects on the eye

toluene-4-sulphonic acid:
Species: Rabbit
Result: Irritation to eyes, reversing within 7 days

Assessment: Irritating to eyes.
Result: Irritating to eyes.

Respiratory or skin sensitisation

Components:

diethylmethylbenzenediamine:
Exposure routes: Skin
Species: Guinea pig
Result: Does not cause skin sensitisation.

cyclohex-1,2-ylenediamine:
Exposure routes: Skin
Species: Guinea pig
Result: negative

4,4'-isopropylidenediphenol:
Exposure routes: Skin
Species: Mouse
Method: OECD Test Guideline 429
Result: Does not cause skin sensitisation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

Exposure routes: Skin
Species: Humans
Assessment: May cause sensitisation by skin contact.
Result: Causes sensitisation.

toluene-4-sulphonic acid:
Exposure routes: Skin
Species: Guinea pig
Method: Directive 67/548/EEC, Annex V, B.6.
Result: Does not cause skin sensitisation.

Assessment: No data available

Germ cell mutagenicity

Components:

diethylmethylbenzenediamine:

Genotoxicity in vitro : Metabolic activation: negative
Method: OECD Test Guideline 476
Result: negative

cyclohex-1,2-ylenediamine:

Genotoxicity in vitro : Concentration: 15 - 1500 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

: Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
GLP: yes

: Concentration: 33 - 1142 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative
GLP: yes

bisphenol A:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Result: negative

toluene-4-sulphonic acid:

Genotoxicity in vitro : Concentration: 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

REN HY 5212

Version Revision Date: SDS Number: Date of last issue: -
1.0 06.04.2017 400001009577 Date of first issue: 06.04.2017

: Concentration: 1902 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Components:

diethylmethylbenzenediamine:
Genotoxicity in vivo

: Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

cyclohex-1,2-ylenediamine:
Genotoxicity in vivo

: Application Route: Inhalation
Exposure time: 13 Weeks
Dose: 1.6 - 160 mg/m³
Method: OECD Test Guideline 474
Result: negative
GLP: yes

Application Route: Oral
Dose: 75 - 750 mg/kg
Method: OECD Test Guideline 475
Result: negative
GLP: yes

bisphenol A:
Genotoxicity in vivo

: Method: OECD Test Guideline 474
Result: negative

toluene-4-sulphonic acid:
Genotoxicity in vivo

: Application Route: Oral
Exposure time: 72 h
Dose: 4467 mg/kg
Method: OECD Test Guideline 474
Result: negative

Application Route: Intraperitoneal injection
Exposure time: 72 h
Dose: 580 mg/kg
Method: In Vivo Mammalian Cytogenics Tests: Erythrocyte
Micronucleus Assay
Result: negative

REN HY 5212

Version Revision Date: SDS Number: Date of last issue: -
1.0 06.04.2017 400001009577 Date of first issue: 06.04.2017

Carcinogenicity

Components:

diethylmethylbenzenediamine:
Species: Rat, (male and female)
Application Route: Oral
Exposure time: 24 month(s)
Dose: 1.8 - 3.2 mg/kg
Frequency of Treatment: 7 daily
Method: OECD Test Guideline 451
Result: negative

bisphenol A:
Species: Rat, (male and female)
Application Route: Oral
Exposure time: 103 weeks
Frequency of Treatment: 7 daily
Result: negative

toluene-4-sulphonic acid:
Species: Rat, (male and female)
Application Route: Oral
Exposure time: 24 month(s)
Dose: >= 240 mg/kg
Frequency of Treatment: 5 daily
Method: OECD Test Guideline 453
Result: negative

Carcinogenicity - Assessment : No data available

Reproductive toxicity

Components:

cyclohex-1,2-ylenediamine:
Effects on fertility : Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 416
GLP: yes

bisphenol A:
Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 416
Result: Embryotoxic effects and adverse effects on the offspring were detected.

Components:

cyclohex-1,2-ylenediamine:
Effects on foetal development : Species: Rat, male and female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
ca. 184 mg/kg body weight
Method: OECD Test Guideline 414

REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

Result: No teratogenic effects
GLP: no

bisphenol A:

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
< 160 mg/kg body weight
Method: OECD Test Guideline 416
Result: No teratogenic effects

toluene-4-sulphonic acid:

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
> 936 mg/kg body weight
Result: No teratogenic effects

Components:

bisphenol A:
Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT - single exposure

Components:

cyclohex-1,2-ylenediamine:
Exposure routes: Inhalation
Target Organs: Respiratory Tract
Assessment: May cause respiratory irritation.

bisphenol A:

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

toluene-4-sulphonic acid:

Target Organs: Respiratory Tract
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

STOT - repeated exposure

Components:

diethylmethylbenzenediamine:
Exposure routes: Ingestion
Target Organs: Pancreas, Liver, Kidney
Assessment: May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

diethylmethylbenzenediamine:
Species: Rat, male and female
NOAEL: 8 - 10 mg/kg
Application Route: Ingestion
Exposure time: 2 160 hMethod: Subchronic toxicity

cyclohex-1,2-ylenediamine:
Species: Rat, male and female
: 16
Test atmosphere: dust/mist
Exposure time: 13 WeeksMethod: OECD Test Guideline 413

bisphenol A:
Species: Dog, male and female
: 75 mg/kg, 10
Application Route: Ingestion
Test atmosphere: dust/mist
Exposure time: 2 160 hNumber of exposures: 7 d
Method: Subchronic toxicity

Species: Rat, male and female
LOAEL: 600 mg/kg
Application Route: Ingestion
Exposure time: 672 hNumber of exposures: 7 d
Method: Subchronic toxicity

toluene-4-sulphonic acid:
Species: Rat, male and female
NOAEL: >= 500 mg/kg
Application Route: Ingestion
Exposure time: 672 hNumber of exposures: 7 d
Method: Subchronic toxicity

Repeated dose toxicity - : No data available
Assessment

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

REN HY 5212

Version Revision Date: SDS Number: Date of last issue: -
1.0 06.04.2017 400001009577 Date of first issue: 06.04.2017

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

diethylmethylbenzenediamine:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 200 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: DIN 38412

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0,5 mg/l
aquatic invertebrates Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae : ErC50 (Desmodesmus subspicatus (Scenedesmus
subspicatus)): ca. 104 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

M-Factor (Acute aquatic : 1
toxicity)

Toxicity to microorganisms : EC50 (Pseudomonas putida): >= 170 mg/l
Exposure time: 24 h
Test Type: static test
Test substance: Fresh water

cyclohex-1,2-ylenediamine:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 200 mg/l

REN HY 5212

Version Revision Date: SDS Number: Date of last issue: -
1.0 06.04.2017 400001009577 Date of first issue: 06.04.2017

Exposure time: 48 h
Test substance: Fresh water
Method: DIN 38412
GLP: yes
Remarks: Toxic to aquatic organisms.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 19,8 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202
GLP: no

Toxicity to algae : EC50 : 29,6 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 4,16 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

bisphenol A:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 7,5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 : 3,9 - 10,2 mg/l
Exposure time: 48 h

(Ceriodaphnia dubia (Water flea)):

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 2,5 - 3,1 mg/l
Exposure time: 96 h

Toxicity to fish (Chronic toxicity) : NOEC: 0,016 mg/l
Exposure time: 444 d
Species: Pimephales promelas (fathead minnow)
Test Type: flow-through test
Test substance: Fresh water
Method: Fish Life Cycle Toxicity
Remarks: Toxic to aquatic organisms.

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment
Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

toluene-4-sulphonic acid:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 325 mg/l

REN HY 5212

Version Revision Date: SDS Number: Date of last issue: -
1.0 06.04.2017 400001009577 Date of first issue: 06.04.2017

Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 103 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 73 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

ErC50 (Desmodesmus subspicatus (Scenedesmus subspicatus)): > 40 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.3.

EC50 (Selenastrum capricornutum (green algae)): >= 758 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water

EC50 (Selenastrum capricornutum (green algae)): >= 230 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water

Toxicity to microorganisms : EC50 (activated sludge): > 650 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 209

12.2 Persistence and degradability

Components:

diethylmethylbenzenediamine:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: < 60 %
Exposure time: 28 d

Result: Not readily biodegradable.
Biodegradation: < 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

REN HY 5212

Version 1.0 Revision Date: 06.04.2017 SDS Number: 400001009577 Date of last issue: -
Date of first issue: 06.04.2017

Photodegradation : Test Type: Air
Rate constant: < .00001

cyclohex-1,2-ylenediamine:
Biodegradability : Result: Readily biodegradable.
Exposure time: 17 d
Method: OECD Test Guideline 301D

Stability in water : Method: No information available.
GLP: No information available.
Remarks: see user defined free text

Photodegradation : Rate constant: < .001
GLP: no

bisphenol A:
Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 - 2 %
Exposure time: 28 d

toluene-4-sulphonic acid:
Biodegradability : Result: Readily biodegradable.
Biodegradation: > 60 %
Exposure time: 28 d

12.3 Bioaccumulative potential

Components:

diethylmethylbenzenediamine:
Bioaccumulation : Bioconcentration factor (BCF): 13,82
Remarks: Bioaccumulation is unlikely.

Bioconcentration factor (BCF): 2,75
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 1,17 (25 °C)
Method: OECD Test Guideline 107

cyclohex-1,2-ylenediamine:
Partition coefficient: n-octanol/water : log Pow: < -0,9 (20 °C)
pH: 7
Method: OECD Test Guideline 107
GLP: yes

toluene-4-sulphonic acid:
Partition coefficient: n-octanol/water : log Pow: 0,41 (25 °C)
Method: Partition coefficient

12.4 Mobility in soil

Components:

diethylmethylbenzenediamine:
Distribution among environmental compartments : Koc: 132 - 170

REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

: Koc: 31,72 - 551

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

IATA

14.1 UN number : UN 2735
14.2 UN proper shipping name : Polyamines, liquid, corrosive, n.o.s.
(1,2-DIAMINO CYCLOHEXANE,
DIETHYLTOLUENEDIAMINE)

14.3 Transport hazard class(es) : 8

14.4 Packing group : II

Labels : Corrosive

Packing instruction (cargo aircraft) : 855

Packing instruction (passenger aircraft) : 851

IMDG

14.1 UN number : UN 2735

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

REN HY 5212

Version 1.0 Revision Date: 06.04.2017 SDS Number: 400001009577 Date of last issue: -
Date of first issue: 06.04.2017

14.2 UN proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(1,2-DIAMINO CYCLOHEXANE,
DIETHYLTOLUENEDIAMINE)

14.3 Transport hazard class(es) : 8

14.4 Packing group : II
Labels : 8
EmS Code : F-A, S-B

14.5 Environmental hazards
Marine pollutant : yes

ADR

14.1 UN number : UN 2735
14.2 UN proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(1,2-DIAMINO CYCLOHEXANE,
DIETHYLTOLUENEDIAMINE)

14.3 Transport hazard class(es) : 8

14.4 Packing group : II
Labels : 8

14.5 Environmental hazards
Environmentally hazardous : yes

RID

14.1 UN number : UN 2735
14.2 UN proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(1,2-DIAMINO CYCLOHEXANE,
DIETHYLTOLUENEDIAMINE)

14.3 Transport hazard class(es) : 8

14.4 Packing group : II
Labels : 8

14.5 Environmental hazards
Environmentally hazardous : yes

Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : bisphenol A

Water contaminating class (Germany) : WGK 2 water endangering

Other regulations:

REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: Not in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

H360F : May damage fertility.
H373 : May cause damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Acute aquatic toxicity
Aquatic Chronic : Chronic aquatic toxicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Repr. : Reproductive toxicity
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure

Further information

Classification of the mixture:

Acute Tox. 4	H302
Acute Tox. 4	H312
Skin Corr. 1A	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Repr. 1B	H360F
STOT SE 3	H335
STOT RE 2	H373
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

REN HY 5212

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	06.04.2017	400001009577	Date of first issue: 06.04.2017

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.