

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name** *NEUKADUR Plastrotherm 130*
- **Utilization of the substance of the formulation:** *Polyol for Polyurethanes*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
*No further relevant information available.*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*Suter Kunststoffe AG  
Aefligenstrasse 3  
CH-3312 Fraubrunnen  
Tel. +41 (0)31 763 60 60  
Fax. +41 (0)31 763 60 61  
e-mail: info@swiss-composite.ch*
- **Further information obtainable from:** *info@swiss-composite.ch*
- **1.4 Emergency telephone number:**  
*Toxikologisches Infozentrum Zuerich  
Tel. 145 (International +41 (0)44 251 51 51)*



**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
*The product is not classified according to the CLP regulation.*
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** *Void*
- **Hazard pictograms** *Void*
- **Signal word** *Void*
- **Hazard statements** *Void*
- **Additional information:**  
*Safety data sheet available on request.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*

**SECTION 3: Composition/information on ingredients**

- **3.2 Chemical characterisation: Mixtures**
- **Description:** *Mixture of substances listed below with nonhazardous additions.*

· **Dangerous components:**

CAS: 770-35-4 EINECS: 212-222-7 Reg.nr.: 01-2119486566-23	<i>1-phenoxypropan-2-ol</i>	 <i>Eye Irrit. 2, H319</i>	<i>2.5-5%</i>
CAS: 25214-63-5 NLP: 500-035-6 Reg.nr.: 01-2119471485-32-xxxx	<i>ethylenediamine, propoxylated</i>	 <i>Eye Irrit. 2, H319</i>	<i>1-2.5%</i>

- **Additional information:** *For the wording of the listed hazard phrases refer to section 16.*

**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **General information:** *Immediately remove any clothing soiled by the product.*
- **After inhalation:**  
*Supply fresh air; consult doctor in case of complaints.*

**Trade name NEUKADUR Plastotherm 130**

(Contd. of page 1)

- In case of unconsciousness place patient stably in side position for transportation.*
- **After skin contact:**  
*Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.*
- **After eye contact:** *Rinse opened eye for several minutes under running water. Then consult a doctor.*
- **After swallowing:**  
*Do not induce vomiting; call for medical help immediately.  
If swallowed, rinse mouth with water (only if the person is conscious).  
A person vomiting while laying on their back should be turned onto their side.  
Seek immediate medical advice.*
- **4.2 Most important symptoms and effects, both acute and delayed** *No further relevant information available.*
- **4.3 Indication of any immediate medical attention and special treatment needed**  
*No further relevant information available.*

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
*CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.*
- **For safety reasons unsuitable extinguishing agents:** *Water with full jet*
- **5.2 Special hazards arising from the substance or mixture**  
*In case of fire, the following can be released:  
Carbon monoxide (CO)  
carbon dioxide*
- **5.3 Advice for firefighters**
- **Protective equipment:**  
*Wear fully protective suit.  
Wear self-contained respiratory protective device.*
- **Additional information**  
*Cool endangered receptacles with water spray.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.*

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
*Particular danger of slipping on leaked/spilled product.  
Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources.  
Ensure adequate ventilation*
- **6.2 Environmental precautions:**  
*Do not allow to enter sewers/ surface or ground water.  
Inform respective authorities in case of seepage into water course or sewage system.*
- **6.3 Methods and material for containment and cleaning up:**  
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*
- **6.4 Reference to other sections**  
*See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.*

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
*Inform personnel of the affiliated with the product hazards and risks  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
Open and handle receptacle with care.  
Ensure good ventilation/exhaustion at the workplace.*

(Contd. on page 3)

**Trade name NEUKADUR Plastotherm 130**

(Contd. of page 2)

- Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
  - Protect from heat.
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
  - Keep container tightly closed and dry and storage in a good ventilated room.
- Storage temperature: 20 - 25 °C.
- **Information about storage in one common storage facility:**
  - Store away from reducing agents.
  - Do not store together with oxidising and acidic materials.
  - Store away from foodstuffs.
- **Further information about storage conditions:**
  - Protect from humidity and water.
  - Store in dry conditions.
  - Protect from frost.
  - This product is hygroscopic.
- **Storage class: 10**
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
  - The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
  - The usual precautionary measures are to be adhered to when handling chemicals.
- **Respiratory protection:**
  - In inadequately ventilated places and during spraying respirator necessary. Recommended to be fresh-air mask or filter combination for short-term work A2-P2
  - Not necessary if room is well-ventilated.
- **Protection of hands:**
  - Preventive skin protection (3-point program) required
  - The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
  - Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
  - Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
  - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
  - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
  - Suitable materials for protective gloves, EN 374-3:
    - Polychloroprene - CR: thickness > = 0.5 mm, breakthrough time > = 480 min.

(Contd. on page 4)

Printing date 18.10.2018

Version number 11

Revision: 18.10.2018

Trade name NEUKADUR Plastotherm 130

(Contd. of page 3)

NBR - NBR: thickness > = 0,35 mm, Breakthrough time > = 480 min.  
 Butyl rubber - IIR: thickness > = 0.5 mm, breakthrough time > = 480 min.  
 Fluorine rubber - FKM: thickness > = 0.4 mm; breakthrough time > = 480 min.  
 Recommendation: Dispose of contaminated gloves ..

## · Eye protection:



Tightly sealed goggles

## · Body protection: Protective work clothing

## \* SECTION 9: Physical and chemical properties

## · 9.1 Information on basic physical and chemical properties

## · General Information

## · Appearance:

Form:	Fluid
Colour:	Whitish
Odour:	Characteristic
Odour threshold:	Not determined.

· pH-value: Not determined.

## · Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.

· Flash point: Not applicable.

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 210 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

## · Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapour pressure: Not determined.

Density at 20 °C:	1,2 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.

· Solubility in / Miscibility with water: Insoluble.

· Partition coefficient: n-octanol/water: Not determined.

## · Viscosity:

Dynamic at 20 °C:	3.900 mPas
Kinematic:	Not determined.

## · Solvent content:

Organic solvents:	0,4 %
VOC (EC)	5.3 g/l

(Contd. on page 5)

Printing date 18.10.2018

Version number 11

Revision: 18.10.2018

Trade name NEUKADUR Plastotherm 130

(Contd. of page 4)

· **9.2 Other information** No further relevant information available.**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
  - Reacts with reducing agents.
  - Reacts with oxidising agents.
  - Reacts with inorganic acid chlorides.
  - No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Incompatible with oxidizing agents, acids
- **10.6 Hazardous decomposition products:**
  - Flammable gases/vapours
  - Carbon monoxide and carbon dioxide

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:****Polyetherpolyol**

Oral	LD50	>2,000 mg/kg (Ratte)
Dermal	LD50	>2,000 mg/kg (Kaninchen)

- **Primary irritant effect:**
- **Skin corrosion/irritation** slightly irritant (OECD method), labelling not required
- **Serious eye damage/irritation** slightly irritant, labelling not required (analogy conclusion)
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:****Polyetherpolyol**

EC50 (48 h)	>100 mg/l (Daphnia Magna)
EC50 (72 h)	>1,000 mg/l (Wasserpflanzen)
EC20(0,5h)	>1,000 mg/l (activated sludge)

- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** Elimination by adsorption onto activated sludge
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 6)

GB

**Trade name NEUKADUR Plastotherm 130**

(Contd. of page 5)

- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Must be specially treated adhering to official regulations.  
Dispose in accordance with applicable international, national and local laws, ordinances and statutes. For disposal within the EC, the appropriate waste code according to the European Waste Catalogue (EWC) should be used.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- |   |                 |
|---|-----------------|
| · <b>14.1 UN-Number</b><br>· <b>ADR, ADN, IMDG, IATA</b>                                    | Void            |
| · <b>14.2 UN proper shipping name</b><br>· <b>ADR, ADN, IMDG, IATA</b>                      | Void            |
| · <b>14.3 Transport hazard class(es)</b><br>· <b>ADR, ADN, IMDG, IATA</b><br>· <b>Class</b> | Void            |
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>                                     | Void            |
| · <b>14.5 Environmental hazards:</b><br>· <b>Marine pollutant:</b>                          | No              |
| · <b>14.6 Special precautions for user</b>  | Not applicable. |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>            | Not applicable. |
| · <b>UN "Model Regulation":</b>   | Void            |

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

(Contd. on page 7)

Trade name NEUKADUR Plastotherm 130

(Contd. of page 6)

· **National regulations:**· **Technical instructions (air):**

Class	Share in %
NK	0.25-1

· **Waterhazard class:** Water hazard class 1 (VwVwS 17.05.99): slightly hazardous for water.· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H319 Causes serious eye irritation.

· **Department issuing SDS:** info@swiss.composite.ch· **Contact:**

Herr Karasmann Tel. +41 (0)31 763 60 60

Herr Ottensmann Tel. +49 (0)2056-25863-7

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

· **\* Data compared to the previous version altered.**