



SAFETY DATA SHEET
(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SD 5503
Product code : 872.
Hardener for epoxy resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Hardener
Uses advised against : data not available

1.3. Details of the supplier of the safety data sheet

Registered company name : Suter Kunststoffe AG
Address : Aefligenstrasse 3, CH-3312 Fraubrunnen
.Telephone : +41 (0)31 763 60 60 Fax : +41 (0)31 763 60 61.
e-mail: info@swiss-composite.ch
Site web : https://www.swiss-composite.ch

1.4. Emergency telephone number : .

Association/Organisation : ToxInfo Zürich, Telefon 145 (International +41 44 251 51 51).

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).
Acute dermal toxicity, Category 4 (Acute Tox. 4, H312).
Skin corrosion, Category 1B (Skin Corr. 1B, H314).
Serious eye damage, Category 1 (Eye Dam. 1, H318).
Skin sensitisation, Category 1 (Skin Sens. 1, H317).
Reproductive toxicity, Category 1B (Repr. 1B, H360).
Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).
This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07



GHS05



GHS09



GHS08

Signal Word :
DANGER

Product identifiers :

EC 500-105-6 POLYALKYL AMINES
EC 220-666-8 3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE
EC 216-032-5 META XYLENE DIAMINE

SD 5503 - 872

EC 201-245-8 BISPHENOL A
EC 268-626-9 POLYETHYLENEPOLYAMINES
CAS 1293368-66-7 FORMALDEHYDE, POLYMERS WITH DIETHYLENETRIAMINE AND STYRENATED PHENOL
EC 223-775-9 3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE
EC 262-975-0 PHENOL, STYRENATED

Additional labeling :

For professional use only.

Hazard statements :

H302 + H312

Harmful if swallowed or in contact with skin.

H314

Causes severe skin burns and eye damage.

H317

May cause an allergic skin reaction.

H360F

May damage fertility.

H411

Toxic to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P264

Wash hands thoroughly after handling.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER/doctor/...

Other information :

2.3. Other hazards

The mixture contains substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 39423-51-3 EC: 500-105-6 REACH: 01-2119556886-20-XXXX POLYALKYL AMINES	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Eye Dam. 1, H318 Aquatic Chronic 2, H411		25 <= x % < 50
CAS: 2855-13-2 EC: 220-666-8 REACH: 01-2119514687-32-XXXX 3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCL OHEXYLAMINE	GHS07, GHS05 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 3, H412		25 <= x % < 50
CAS: 1477-55-0 EC: 216-032-5 REACH: 01-2119480150-50-XXXX META XYLENE DIAMINE	GHS07, GHS05 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 Acute Tox. 4, H332 Aquatic Chronic 3, H412	[1]	10 <= x % < 25

SD 5503 - 872

CAS: 80-05-7 EC: 201-245-8 REACH: 01-2119457856-23-XXXX BISPHENOL A	GHS05, GHS09, GHS07, GHS08 Dgr Skin Sens. 1, H317 Eye Dam. 1, H318 STOT SE 3, H335 Repr. 1B, H360F Aquatic Chronic 2, H411	[1] [2] [6]	2.5 <= x % < 10
CAS: 68131-73-7 EC: 268-626-9 REACH: 01-2119485823-28-XXXX POLYETHYLENEPOLYAMINES	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		2.5 <= x % < 10
INDEX: 601-053-00-8 CAS: 84852-15-3 EC: 284-325-5 4-NONYLPHENOL, BRANCHED	GHS08, GHS05, GHS07, GHS09 Dgr Repr. 2, H361fd Acute Tox. 4, H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1	[2] [6]	1 <= x % < 2.5
CAS: 1293368-66-7 FORMALDEHYDE, POLYMERS WITH DIETHYLENETRIAMINE AND STYRENATED PHENOL	GHS05, GHS07 Dgr Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318		1 <= x % < 2.5
CAS: 4067-16-7 EC: 223-775-9 REACH: 01-219485826-22-XXXX 3,6,9,12-TETRA-AZATETRADECAMETHYLE NEDIAMINE	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 2, H411		1 <= x % < 2.5
CAS: 61788-44-1 EC: 262-975-0 PHENOL, STYRENATED	GHS07, GHS09 Wng Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411		0 <= x % < 1

Information on ingredients :

- [1] Substance for which maximum workplace exposure limits are available.
- [2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.
- [6] Substances of very high concern (SVHC).

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

If inhaled, move the patient to fresh air and keep warm and rest.
If breathing is irregular or stopped, that qualified personnel provide artificial respiration and call a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.
Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

SD 5503 - 872

Flush with large amounts of water. Remove contact lenses if the victim is. Continue to rinse. Seek medical attention if symptoms persist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor :

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to remain under medical supervision for 48 hours.

Contact a specialist for treatment poisoning if large quantities have been ingested or inhaled.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- nitrogen oxide (NO)
- nitrogen dioxide (NO₂)

5.3. Advice for firefighters

Firefighters should wear suitable protective clothing and a respirator mask with self- full operated in positive pressure mode.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

SD 5503 - 872

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

Avoid exposure to pregnant women and warn women of child-bearing age of the possible risks

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid exposure - obtain special instructions before use.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep away from food and drink, including those for animals.

Store in original container protected from direct sunlight in a dry, cool and well ventilated area away from heat sources.

Keep container tightly closed in a dry place.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

Recommended application area: wood system

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2017/164/UE, 2009/161/UE, 2006/15/CE, 2000/39/CE, 98/24/CE)

CAS	VME-mg/m3	VME-ppm	VLE-mg/m3	VLE-ppm	Notes
80-05-7	2	-	-	-	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA	STEL	Ceiling	Definition	Criteria
1477-55-0			0,1 mg/m3	Skin	

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME	VME	Excess	Notes
-----	-----	-----	--------	-------

SD 5503 - 872

80-05-7		5 E mg/m3		1()
---------	--	-----------	--	-----

- France (INRS - ED984 :2012) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
1477-55-0	-	-	-	0.1	-	-
80-05-7		10	-	-	R2	

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

Final use:

Exposure method:
 Potential health effects:
 DNEL :

Workers.

Dermal contact.
 Long term systemic effects.
 0.91 mg/kg body weight/day

Exposure method:
 Potential health effects:
 DNEL :

Dermal contact.
 Long term local effects.
 0.044 mg of substance/cm2

Exposure method:
 Potential health effects:
 DNEL :

Inhalation.
 Short term systemic effects.
 8550 mg of substance/m3

Exposure method:
 Potential health effects:
 DNEL :

Inhalation.
 Long term systemic effects.
 1.59 mg of substance/m3

Final use:

Exposure method:
 Potential health effects:
 DNEL :

Consumers.

Ingestion.
 Short term systemic effects.
 32 mg/kg body weight/day

Exposure method:
 Potential health effects:
 DNEL :

Ingestion.
 Long term systemic effects.
 0.65 mg/kg body weight/day

Exposure method:
 Potential health effects:
 DNEL :

Dermal contact.
 Short term systemic effects.
 13 mg/kg body weight/day

Exposure method:
 Potential health effects:
 DNEL :

Dermal contact.
 Short term local effects.
 1.59 mg of substance/cm2

Exposure method:
 Potential health effects:
 DNEL :

Dermal contact.
 Long term systemic effects.
 0.4 mg/kg body weight/day

Exposure method:
 Potential health effects:
 DNEL :

Dermal contact.
 Long term local effects.
 0.68 mg of substance/cm2

Exposure method:
 Potential health effects:
 DNEL :

Inhalation.
 Short term systemic effects.
 2542 mg of substance/m3

SD 5503 - 872

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 0.46 mg of substance/m3

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Final use:

Workers.

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 0.91 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Long term local effects.
DNEL : 0.44 mg of substance/cm2

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 8550 mg of substance/m3

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 1.59 mg of substance/m3

Final use:

Consumers.

Exposure method: Ingestion.
Potential health effects: Short term systemic effects.
DNEL : 32 mg/kg body weight/day

Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 0.65 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Short term systemic effects.
DNEL : 13 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Short term local effects.
DNEL : 1.59 mg of substance/cm2

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 0.4 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Long term local effects.
DNEL : 0.68 mg of substance/cm2

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 2542 mg of substance/m3

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.

SD 5503 - 872

DNEL : 0.46 mg of substance/m3

BISPHENOL A (CAS: 80-05-7)

Final use:

Exposure method:

Potential health effects:

DNEL :

Workers.

Dermal contact.

Short term systemic effects.

1.4 mg/kg body weight/day

Exposure method:

Potential health effects:

DNEL :

Dermal contact.

Long term systemic effects.

1.4 mg/kg body weight/day

Exposure method:

Potential health effects:

DNEL :

Inhalation.

Short term systemic effects.

10 mg of substance/m3

Exposure method:

Potential health effects:

DNEL :

Inhalation.

Long term systemic effects.

10 mg of substance/m3

Final use:

Exposure method:

Potential health effects:

DNEL :

Man exposed via the environment.

Ingestion.

Short term systemic effects.

0.05 mg/kg body weight/day

Exposure method:

Potential health effects:

DNEL :

Ingestion.

Long term systemic effects.

0.05 mg/kg body weight/day

Exposure method:

Potential health effects:

DNEL :

Dermal contact.

Short term systemic effects.

0.7 mg/kg body weight/day

Exposure method:

Potential health effects:

DNEL :

Dermal contact.

Long term systemic effects.

0.7 mg/kg body weight/day

Exposure method:

Potential health effects:

DNEL :

Inhalation.

Short term systemic effects.

5.0 mg of substance/m3

Exposure method:

Potential health effects:

DNEL :

Inhalation.

Long term systemic effects.

0.25 mg of substance/m3

Exposure method:

Potential health effects:

DNEL :

Inhalation.

Long term local effects.

5 mg of substance/m3

Exposure method:

Potential health effects:

DNEL :

Inhalation.

Short term local effects.

5 mg of substance/m3

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

SD 5503 - 872

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Inhalation.
Short term systemic effects.
20.1 mg of substance/m³

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Short term local effects.
20.1 mg of substance/m³

Final use:

Exposure method:
Potential health effects:
DNEL :

Man exposed via the environment.

Ingestion.
Long term systemic effects.
0.526 mg/kg body weight/day

POLYALKYL AMINES (CAS: 39423-51-3)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
1.6 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
14 mg of substance/m³

Final use:

Exposure method:
Potential health effects:
DNEL :

Consumers.

Dermal contact.
Long term systemic effects.
0.8 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
3.48 mg of substance/m³

Predicted no effect concentration (PNEC):

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

Environmental compartment:
PNEC : Soil.
0.18 mg/kg

Environmental compartment:
PNEC : Fresh water.
2.5 µg/l

Environmental compartment:
PNEC : Sea water.
2.5 µg/l

Environmental compartment:
PNEC : Fresh water sediment.
0.22 mg/kg

Environmental compartment:
PNEC : Marine sediment.
0.14 mg/kg

Environmental compartment:
PNEC : Waste water treatment plant.
1.64 mg/l

POLYETHYLENEDIAMINES (CAS: 68131-73-7)

SD 5503 - 872

Environmental compartment: PNEC :	Soil. 10 mg/kg
Environmental compartment: PNEC :	Fresh water. 1.6 µg/l
Environmental compartment: PNEC :	Sea water. 1.6 µg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.14 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.14 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 3.19 mg/l
BISPHENOL A (CAS: 80-05-7)	
Environmental compartment: PNEC :	Soil. 3.7 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.018 mg/l
Environmental compartment: PNEC :	Sea water. 0.016 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 2.2 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 320 mg/l
3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)	
Environmental compartment: PNEC :	Soil. 1.121 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.06 mg/l
Environmental compartment: PNEC :	Sea water. 0.006 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 0.23 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 5.784 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.578 mg/kg
Environmental compartment:	Waste water treatment plant.

SD 5503 - 872

PNEC :	3.18 mg/l
POLYALKYLAMINES (CAS: 39423-51-3)	
Environmental compartment:	Soil.
PNEC :	0.002 mg/kg
Environmental compartment:	Fresh water.
PNEC :	0.0044 mg/l
Environmental compartment:	Sea water.
PNEC :	0.00044 mg/l
Environmental compartment:	Intermittent waste water.
PNEC :	0.044 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	0.02 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.002 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	10 mg/l

8.2. Exposure controls

Use only with adequate ventilation or provided with ventilation at the source.

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Butyl Rubber (Isobutylene-isoprene copolymer)

SD 5503 - 872

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

Mask with filter type A, B, E, K, P

Attention! If the protection group is insufficient.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Fluid liquid.

Color: yellow

Important health, safety and environmental information

pH : Not stated.
Slightly basic.

Boiling point/boiling range : Not relevant.

Flash Point Interval : FP > 100°C.

Vapour pressure (50°C) : Not relevant.

Density : 1.06 ± 0.02 @ 20°C

Water solubility : Soluble.

Viscosity : 117.5 ± 22.5 mPa.s @ 25°C

Melting point/melting range : Not relevant.

Self-ignition temperature : Not relevant.

Decomposition point/decomposition range : Not relevant.

Index of refraction : 1.5045 ± 0.002 @ 25 °C

% VOC : 0

9.2. Other information

Miscibility Alcohols, aromatic solvents

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- humidity

SD 5503 - 872

10.5. Incompatible materials

Keep away from :

- strong oxidising agents

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- nitrogen oxide (NO)
- nitrogen dioxide (NO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Harmful if swallowed.

Harmful in contact with skin.

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure between three minutes and one hour.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

May cause an allergic reaction by skin contact.

Presumed human reproductive toxicant.

May damage fertility.

11.1.1. Substances

Acute toxicity :

PHENOL, STYRENATED (CAS: 61788-44-1)

Oral route :

LD50 > 2000 mg/kg

Species : Rat

OECD Guideline 423 (Acute Oral toxicityAcute Toxic Class Method)

Dermal route :

LD50 > 2000 mg/kg

Species : Rat

OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (n/a) :

LC50 = 4.9 mg/l

OECD Guideline 403 (Acute Inhalation Toxicity)

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

Oral route :

LD50 = 1600 mg/kg

Species : Rat

BISPHENOL A (CAS: 80-05-7)

Oral route :

LD50 = 3250 mg/kg

Species : Rat

Dermal route :

LD50 = 3000 mg/kg

Species : Rabbit

META XYLENE DIAMINE (CAS: 1477-55-0)

Oral route :

LD50 = 1040 mg/kg

Species : Rat

Inhalation route (n/a) :

LC50 = 2.4 mg/l

Species : Rat

SD 5503 - 872

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

Oral route : LD50 = 1030 mg/kg
Species : Rat

Dermal route : LD50 > 2000 mg/kg
Species : Rat
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (n/a) : LC50 > 5.01 mg/l
Species : Rat
OECD Guideline 403 (Acute Inhalation Toxicity)

POLYALKYL AMINES (CAS: 39423-51-3)

Oral route : LD50 = 550 mg/kg
Species : Rat

Dermal route : LD50 > 1000 mg/kg
Species : Rat

Skin corrosion/skin irritation :

PHENOL, STYRENATED (CAS: 61788-44-1)
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

META XYLENE DIAMINE (CAS: 1477-55-0)
Corrosivity : Causes severe skin burns.
Species : Rat

POLYALKYL AMINES (CAS: 39423-51-3)
Species : Rabbit
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Species : Rabbit
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Respiratory or skin sensitisation :

BISPHENOL A (CAS: 80-05-7)
Species : Guinea pig

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)
Species : Rabbit
OECD Guideline 406 (Skin Sensitisation)

META XYLENE DIAMINE (CAS: 1477-55-0)
May cause an allergic skin reaction.
Local lymph node stimulation test : Sensitiser.
OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity :

PHENOL, STYRENATED (CAS: 61788-44-1)
Mutagenesis (in vivo) : Negative.
OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
OECD Guideline 471 (Bacterial Reverse Mutation Assay)

SD 5503 - 872

Ames test (in vitro) : Negative.

POLYETHYLENEDIAMINES (CAS: 68131-73-7)
Mutagenesis (in vivo) : Negative.

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)
No mutagenic effect.

Mutagenesis (in vivo) : Negative.

META XYLENE DIAMINE (CAS: 1477-55-0)
No mutagenic effect.

Reproductive toxicant :

BISPHENOL A (CAS: 80-05-7)
May damage fertility.

META XYLENE DIAMINE (CAS: 1477-55-0)
No toxic effect for reproduction

POLYALKYL AMINES (CAS: 39423-51-3)
Study on development : Species : Rat
OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

Specific target organ systemic toxicity - repeated exposure :

POLYALKYL AMINES (CAS: 39423-51-3)
Dermal route : C > 160 mg/kg bodyweight/jour
Duration of exposure : 90 days
OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

POLYETHYLENEDIAMINES (CAS: 68131-73-7)
Species : Rat

META XYLENE DIAMINE (CAS: 1477-55-0)
Oral route : C = 600 mg/kg bodyweight/day
Species : Rat
Duration of exposure : 28 days
OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

POLYALKYL AMINES (CAS: 39423-51-3)
Algae toxicity : EC50 = 1 mg/l
Duration of exposure : 72 h

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)
Fish toxicity : LC50 = 110 mg/l

SD 5503 - 872

	Species : Leuciscus idus Duration of exposure : 96 h
Crustacean toxicity :	EC50 = 23 mg/l Species : Daphnia magna Duration of exposure : 48 h OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
	NOEC = 3 mg/l Species : Daphnia magna Duration of exposure : 21 days OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Algae toxicity :	ECr50 > 50 mg/l Species : Desmodesmus subspicatus Duration of exposure : 72 h
	NOEC = 1.5 mg/l Species : Desmodesmus subspicatus Duration of exposure : 72 h Other guideline
PHENOL, STYRENATED (CAS: 61788-44-1)	
Fish toxicity :	LC50 = 14.8 mg/l Duration of exposure : 96 h OECD Guideline 203 (Fish, Acute Toxicity Test)
Crustacean toxicity :	EC50 <= 10 mg/l Species : Daphnia magna Duration of exposure : 48 h OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
	NOEC = 0.115 mg/l Duration of exposure : 21 days OECD Guideline 211 (Daphnia magna Reproduction Test)
Algae toxicity :	ECr50 = 3.14 mg/l Duration of exposure : 72 h OECD Guideline 201 (Alga, Growth Inhibition Test)
3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)	
Fish toxicity :	LC50 = 180 mg/l Duration of exposure : 96 h
Crustacean toxicity :	EC50 = 17.5 mg/l Duration of exposure : 48 h
	NOEC = 0.8 mg/l Duration of exposure : 14 days
Algae toxicity :	ECr50 = 0.7 mg/l Duration of exposure : 72 h
	NOEC = 0.25 mg/l

SD 5503 - 872

Duration of exposure : 72 h

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Fish toxicity : LC50 = 100 mg/l
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 2.2 mg/l
Species : Daphnia magna
Duration of exposure : 48 h

Algae toxicity : ECr50 = 0.23 mg/l
Duration of exposure : 72 h

Aquatic plant toxicity : ECr50 = 319.3 mg/l
Duration of exposure : 48 h

BISPHENOL A (CAS: 80-05-7)

Fish toxicity : LC50 = 4.6 mg/l
Species : Pimephales promelas
Duration of exposure : 96 h

NOEC = 0.016 mg/l
Species : Others

Crustacean toxicity : EC50 = 7.75 mg/l
Species : Others
Duration of exposure : 48 h

NOEC = 1.8 mg/l

Algae toxicity : ECr50 = 2.73 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 96 h

META XYLENE DIAMINE (CAS: 1477-55-0)

Fish toxicity : LC50 = 87.6 mg/l
Duration of exposure : 96 h
OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity : EC50 = 15.2 mg/l
Duration of exposure : 48 h
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity : ECr50 = 20.3 mg/l
Species : Scenedesmus subspicatus
Duration of exposure : 72 h
OECD Guideline 201 (Alga, Growth Inhibition Test)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

PHENOL, STYRENATED (CAS: 61788-44-1)

SD 5503 - 872

Biodegradability :	Non-rapidly degradable.
3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7) Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
POLYETHYLENEDIAMINES (CAS: 68131-73-7) Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
BISPHENOL A (CAS: 80-05-7) Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
META XYLENE DIAMINE (CAS: 1477-55-0) Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2) Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
POLYALKYL AMINES (CAS: 39423-51-3) Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

12.3.1. Substances

PHENOL, STYRENATED (CAS: 61788-44-1) Octanol/water partition coefficient :	log K _{ow} ≤ 5.8 OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Bioaccumulation :	BCF ≤ 190 OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
BISPHENOL A (CAS: 80-05-7) Octanol/water partition coefficient :	log K _{ow} = 3.3
Bioaccumulation :	BCF = 73
3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2) Octanol/water partition coefficient :	log K _{ow} = 0.99 OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK) :

WGK 3 (VwVwS vom 27/07/2005, KBws) : Extremely hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

07 01 08 * other still bottoms and reaction residues

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

14.1. UN number

2735

14.2. UN proper shipping name

UN2735=AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(meta xylene diamine, polyalkyl amines)

14.3. Transport hazard class(es)

- Classification :



8

14.4. Packing group

III

14.5. Environmental hazards

- Environmentally hazardous material :



14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C7	III	8	80	5 L	274	E1	3	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	8	-	III	5 L	F-A,S-B	223 274	E1

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	8	-	III	852	5 L	856	60 L	A3 A803	E1
	8	-	III	Y841	1 L	-	-	A3 A803	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.
For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

- Container information:

No data available.

Usage restrictions apply to the product : See annex XVII of EC regulation No. 1907/2006.

For professional users only.

- Particular provisions :


No data available.

- German regulations concerning the classification of hazards for water (WGK) :

WGK 3 (VwVwS vom 27/07/2005, KBws) : Extremely hazardous for water.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :

NFPA 704, Labelling: Health=3 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H302 + H312	Harmful if swallowed or in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360F	May damage fertility.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.

SD 5503 - 872

H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS05 : Corrosion

GHS07 : Exclamation mark

GHS08 : Health hazard

GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.