

# SAFETY DATA SHEET

ULTRA LIGHT HÄRTER FAST

Page: 1

Compilation date: 22.02.2018

Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** ULTRA LIGHT HÄRTER FAST

**Product code:** NPH

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** Filler for industrial or professional application. For information regarding additional possible application please email us or dial the indicated phone number as shown below. We will connect you with our responsible technical personnel.

### 1.3. Details of the supplier of the safety data sheet

**Company name:** Suter Kunststoffe AG  
Aeffigenstrasse 3  
CH-3312 Fraubrunnen  
Schweiz

**Tel:** +41 (0)31 763 60 60

**Fax:** +41 (0)31 763 60 61

**Email:** info@swiss-composite.ch

### 1.4. Emergency telephone number

**Emergency tel:** ToxInfo Suisse, Tel. 145, International +41 (0)44 251 51 51

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Acute Tox. 4: H302; Aquatic Chronic 3: H412; Muta. 2: H341; Skin Corr. 1B: H314; Skin Sens. 1: H317

**Most important adverse effects:** Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects. Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

**Label elements:**

**Hazard statements:** H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H341: Suspected of causing genetic defects.

H412: Harmful to aquatic life with long lasting effects.

**Hazard pictograms:** GHS05: Corrosion

[cont...]

# SAFETY DATA SHEET

ULTRA LIGHT HÄRTER FAST

Page: 2

GHS07: Exclamation mark

GHS08: Health hazard



**Signal words:** Danger

**Precautionary statements:** P102: Keep out of reach of children.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+312: IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+352: IF ON SKIN: Wash with plenty of water/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+313: If skin irritation or rash occurs: Get medical.

P363: Wash contaminated clothing before reuse.

P405: Store locked up.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

ALIPHATISCHES POLYAMIN - REACH registered number(s): Nicht bestimmt

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	-	-	Aquatic Chronic 4: H413	40-60%

M-XYLYLENDIAMIN - REACH registered number(s): 01-2119480150-50

-	1477-55-0	-	Acute Tox. 4: H302; Aquatic Chronic 3: H412; Skin Corr. 1B: H314; Skin Sens. 1: H317; Acute Tox. 4: H332	1-10%
---	-----------	---	--	-------

BENZYL ALCOHOL - REACH registered number(s): 01-2119492630-38

202-859-9	100-51-6	-	Acute Tox. 4: H332; Acute Tox. 4: H302	1-10%
-----------	----------	---	--	-------

[cont...]

# SAFETY DATA SHEET

ULTRA LIGHT HÄRTER FAST

Page: 3

POLYOXYPROPYLENEDIAMINE - REACH registered number(s): 01-2119557899-12

-	9046-10-0	-	Skin Corr. 1B: H314	1-10%
---	-----------	---	---------------------	-------

PHENOL - REACH registered number(s): 01-2119471329-32

203-632-7	108-95-2	-	Muta. 2: H341; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Skin Corr. 1B: H314	1-10%
-----------	----------	---	--	-------

LOW BOILING POINT NAPHTHA - UNSPECIFIE SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. - REACH registered number(s): 01-2119455851-35

265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	1-10%
-----------	------------	---	---	-------

N-OCTYLAMIN - REACH registered number(s): 01-2119474880-31

-	111-86-4	-	Flam. Liq. 3: H226; Acute Tox. 3: H301; Acute Tox. 4: H332; STOT SE 3: H335; Skin Corr. 1A: H314; Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Acute Tox. 3: H311	0,10-1%
---	----------	---	--	---------

## Section 4: First aid measures

### 4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

### 4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
- Eye contact:** Corneal burns may occur. May cause permanent damage.
- Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

[cont...]

**SAFETY DATA SHEET**  
ULTRA LIGHT HÄRTER FAST

Page: 4

**4.3. Indication of any immediate medical attention and special treatment needed**

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** Corrosive. In combustion emits toxic fumes.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**6.4. Reference to other sections**

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Coated steel.

**7.3. Specific end use(s)**

[cont...]

**SAFETY DATA SHEET**  
ULTRA LIGHT HÄRTER FAST

Page: 5

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**PHENOL**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	2 ppm	4 ppm	-	-

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Nitrile gloves. Breakthrough time of the glove material > 8 hours. Rubber gloves-  
thickness: 0,4 mm

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**Environmental:** Ensure all engineering measures mentioned in section 7 of SDS are in place.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** Grey

**Solubility in water:** Not miscible

**Also soluble in:** Most organic solvents.

**Viscosity:** Non-viscous

**Boiling point/range°C:** n.V.

**Melting point/range°C:** n.V.

**Flammability limits %: lower:** n.V.

**upper:** n.V.

**Flash point°C:** 100

**Part.coeff. n-octanol/water:** n.V.

**Autoflammability°C:** n.a.

**Vapour pressure:** n.V.

**Relative density:** 0,5-0,7 g/cm<sup>3</sup>

**pH:** n.a.

**VOC g/l:** 76

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

[cont...]

**SAFETY DATA SHEET**  
ULTRA LIGHT HÄRTER FAST

Page: 6

**10.1. Reactivity**

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Hazardous ingredients:**

**BENZYL ALCOHOL**

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

**PHENOL**

ORL	MUS	LD50	270	mg/kg
ORL	RAT	LD50	317	mg/kg
SCU	RAT	LD50	460	mg/kg

**LOW BOILING POINT NAPHTHA - UNSPECIFIE SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.**

ORL	RAT	LD50	8400	mg/kg
-----	-----	------	------	-------

**Toxicity values:** No data available.

**Symptoms / routes of exposure**

**Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

**Eye contact:** Corneal burns may occur. May cause permanent damage.

**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

[cont...]

**SAFETY DATA SHEET**  
ULTRA LIGHT HÄRTER FAST

Page: 7

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:** No data available.

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Readily absorbed into soil.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 08 04 09

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN1759

**14.2. UN proper shipping name**

**Shipping name:** CORROSIVE SOLID,  
(M-XYLYLENDIAMIN; POLYOXYPROPYLENEDIAMINE; PHENOL)

**14.3. Transport hazard class(es)**

**Transport class:** 8

**14.4. Packing group**

**Packing group:** II

**14.5. Environmental hazards**

**Environmentally hazardous:** No

**Marine pollutant:** No

[cont...]

**SAFETY DATA SHEET**  
ULTRA LIGHT HÄRTER FAST

Page: 8

**14.6. Special precautions for user**

Tunnel code: E

Transport category: 2

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Specific regulations: Not applicable.

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H226: Flammable liquid and vapour.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H341: Suspected of causing genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

H413: May cause long lasting harmful effects to aquatic life.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.