

<b>Name of peel ply</b>	<b>WT 64 WR PAD</b>
<b>Product reference no.</b>	306402100
<b>Material type</b>	100 % Nylon 6.6 (Polyamide) scoured heat set finished weave plain
<b>Weight</b> CSN EN 12127	64 g/m <sup>2</sup> +/- 5 %
<b>Thickness</b> CSN EN ISO 5084	min. 0,11 mm
<b>Color</b>	white with red stripes (stripes every ca. 30 mm along the warp)
<b>Standard roll sizes</b> CSN EN 1773	min. 1,50 m (from 0,02 m up to 3 m wide available on order)
<b>Standard roll length</b>	min. 100 m ( up to 300 m)
<b>Melt point</b>	250 °C
<b>Softening point</b>	235 °C
<b>pH</b> CSN EN 1413	5.0 – 7.0
<b>Extractable materials</b> CSN 80 0523	max. 0,5 %
<b>Tensile strength</b> CSN EN ISO 13934-1	
<b>warp</b>	min. 430 Newtons
<b>fill</b>	min. 390 Newtons
<b>Fabric construction</b> CSN EN 1049-2	
<b>warp</b>	36 ends/cm +/- 5 %
<b>fill</b>	28 picks/cm +/- 5 %

We consider the information contained in this data sheet to be correct, the information is supported by tests we believe to be reliable, however we cannot guarantee their accuracy. The customer shall decide upon the suitability of this product for their needs and assume all risks and liabilities associated with the use of this product.